



NOTES:

1. REFER TO JOHNS MANVILLE WEBSITE (www.jm.com) FOR MOST UP-TO-DATE INFORMATION.
2. ANY CARPENTRY, METAL WORK, OR MASONRY CONSTRUCTION SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
3. EXTEND ALL PLIES TO EDGE OF DRAIN BOWL.
4. REMOVE DRAIN CLAMPING RING FOR INSTALLATION OF FIELD SYSTEM. RE-INSTALL DRAIN CLAMPING RING AFTER SYSTEM HAS CURED.
5. JM COATING FLASHING CONSISTS OF JM COATING UNIVERSAL BASE, JM COATING POLYESTER REINFORCING FABRIC AND JM COATING SILICONE FLASHING.
6. FOR JM COATING SILICONE FIELD SYSTEM 5 AND 10 YEAR GUARANTEE TERMS, USE THE APPROPRIATE APPLICATION REQUIREMENTS. REFER TO JM COATING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.

DRAWING NO.	
CS-DV-01	
SCALE	ISSUE DATE
N.T.S	01-23-19

ROOF DRAIN FLASHING RESTORATION	
MEMBRANE TYPE: JM COATING - SILICONE	
MAXIMUM GUARANTEE TERM:	

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

