

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
Insulation							
Fasteners							
Nail-Lok™ WD	Nailboard (Regular and Vented) Fastener for use with wood decks.	X	X	Wood	Black	4½" to 10" (11.4 cm to 25.4 cm) in ½" (1.3 cm) increments 11" to 16" (27.9 cm to 40.6 cm) in 1" (2.5 cm) increments	250/pail
Nail-Lok™ SD	Nailboard (Regular and Vented) Fastener for use with steel decks.	X	X	Metal (18-24 ga.) Structural Concrete	Black	3" to 8" (7.6 cm to 20.3 cm) in ½" (1.3 cm) increments 8" to 12" (20.3 cm to 30.5 cm) in 2" (5.1 cm) increments	250/pail
UltraFast® Fastener	#12 case-hardened steel, polymer-coated fastener.	X	X	Metal (18-24 ga.) Wood	Blue	1½" to 8" (4.13 cm to 20.32 cm) (1) #3 Phillips bit in each pail (1) ¼" (6.35 mm) hex head bit per 3 pails	1,000/pail
Plates							
UltraFast® Plate (Metal)	Recessed round or square flat-bottomed plate. Compatible with UltraFast® and All Purpose Fasteners.	X	X	Metal (18-22 ga.) Wood	Grey	3" (76 mm) round or square	1,000/pail
UltraFast® Plate (Locking Plastic)	High strength polypropylene plates with a special locking feature. Compatible with UltraFast® and All Purpose Fasteners.	X	X	Metal (18-22 ga.) Wood	Blue	3" (76 mm) round	1,000/pail
Fastener and Plate Systems							
Lite-Deck Fasteners and Plates	Insulation Fasteners and plates.	X	X	Cementitious Wood Fiber Gypsum	Black (fasteners) Grey (plates)	Fastener lengths: 2.6" to 12" (6.7 cm to 30.5 cm) Plates: 3" (7.6 cm) round	Quantities vary by fastener length. Plates 500/box
UltraFast® AccuTrac™ Fastener and Plate System	Insulation fastening system.	X	X	Metal (18-24 ga.) Wood	Blue (fasteners) Grey (plates)	Fastener lengths: 1½" to 6" (4.13 cm to 15.24 cm) Plate: 3" (76 mm) square	Fasteners: 1,000/pail Plates: 1,000/pail
UltraFast® Pre-Assembled Fasteners and Plates	Polymer-coated fastener with Galvalume®-Metal or Locking Plastic Plates.	X	X	Metal (18-24 ga.) Wood	Blue (fasteners) Grey (metal plates) Blue (plastic plates)	Fasteners length: 1.6" to 8" (4.13 cm to 20.32 cm) (A bit is provided in each box) Plates: 3" (7.6 cm) Round Metal or Plastic	1,000/box

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
Membrane							
Fasteners							
Extra High Load Fasteners	#21 fasteners with a corrosion-resistant coating.	X		Metal (18-24 ga.) Wood	Black	2" to 3" (5.1 cm to 7.6 cm) 4" to 6" (10.2 cm to 15.2 cm) 7" to 8" (17.8 cm to 20.32 cm)	2" to 3" - 1,000/pail 4" to 6" - 500/pail 7" to 8" - 250/pail
High Load Fasteners	#15 case-hardened steel roof membrane fastener and Galvalume®-coated steel seam plates.	X	X	Metal (18-24 ga.) Wood	Blue	1¼" to 24" (3.2 cm to 61 cm)	Quantities vary by fastener length.
High Load LH Fastener	#15 case-hardened steel roof membrane fastener with Galvalume®-coated steel seam plates.	X	X	Metal (18-24 ga.) Wood	Grey	1¼"-12" (3.2cm to 30.5cm)	Quantities vary by fastener length.
JM Purlin Fastener	Steel-coated roof membrane fastener with a 1/4" hex head and 3/4" drill point.	X		Metal Purlins (12-18 ga.)	Grey	3¾" (9.53 cm) 4¾" (12.07 cm) 5¾" (14.61 cm) 7" (17.78 cm) 8" (20.32 cm)	500/pail
Plates							
APB Plates	Galvalume®-coated steel round plate with barbs.	X		Metal (18-24 ga.) Wood Structural Concrete	Grey	2" (5.1 cm) round	1,000/pail
Anchor Disc	Anchor Discs are 2" (5.1 cm) diameter, round, Galvalume®-coated steel discs. Please contact your JM sales representative for information regarding this product.		X			2" (51 mm) round	1,000/box
Extra High Load Plates	#3 Phillips head and a drill point.	X			Grey	3" (7.6 cm) round	500/pail
ENRGY® Anchor	Photovoltaic solution replacing ballast in traditional rail-mounted systems.	X	X	Dependent on system	Grey	Membrane Dimensions: 11.75" x 11.75" (30 cm x 30cm) Plate Dimensions: 5.5" (14 cm) round	25/box
High Load Plates	#15 case-hardened steel roof membrane fastener and Galvalume®-coated steel seam plates.	X	X		Grey	2 ¾" (60 mm) round	1,000/pail
High Load Plus Plates	High Load Plus Plates are heavy duty Galvalume®-coated steel seam plates with barbs.	X	X		Grey	2¾" (7 cm) round	500/pail

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
JM 90 Seam Plate	JM 90 Seam Plate are heavy duty Galvalume®-coated steel seam plates with eye hooks.	X	X		Grey	3" (7.62 cm)	2½"-8" - 500/pail 9"-10" - 250/pail
UltraFast® Plus Plate	Galvalume®-coated steel 3" nominal square plate used with UltraFast #12 or #14 fasteners.	X		Metal (18-22 ga.) Wood	Grey	3" (7.62 cm) nominal Square	1,000/pail
Fastener and Plate Systems							
High Load AccuSeam™ System	Premier one-step, automated, single-ply membrane seam-fastening system.	X		Metal (18-24 ga.) Wood	Black (fasteners) Grey (plates)	Fastener Sizes: 1¼" to 24" (3.2 cm to 61 cm) 2 ⅜" Plates	Quantities vary by fastener length.
Lightweight Concrete Base Sheet Pre-Assembled Fastener and Plate	Twin-legged, expanding fastener with Galvalume®-coated steel plate.		X	Lightweight Insulated Concrete Gypsum	Black	Fastener lengths: 1.2" (31 mm) and 1.7" (43 mm) Plate: 2.7" (69 mm) round	1.2" - 1,000/box 1.7" - 500/box
JM Termination Systems	Single ply membrane fastening systems include termination bars, anchor discs and masonry nail-in anchors.	X	X	Metal (18-24 ga.) Wood	Various	Termination Bar: 1.35' x 10' (34 mm x 3.05 m) strips Anchor Disc: 2" (51 mm) diameter Fastener: 1¼" (32 mm) Nail-In Anchor: 1¼" (32 mm) diameter	Termination Bar: 500/tube Anchor Disc: 1,000/box Fastener: 1,000/pail Nail-In Anchor: 1,000/box
Membrane Battens	1" wide, prepunched, polymer batten strips with prepunched, counter-sunk, Galvalume®-coated steel anchor bars.	X		Metal (18-24 ga.) Wood Structural Concrete	White (Battens) Grey (Anchor Bars)	Polymer Batten Strip: 1" (2.54 cm) wide .05" (1.27 mm) thick Anchor Bars: 1" (2.54 cm) wide 10' (3.05 m) length	Polymer Batten Strip: 250' (76.2 m)/carton Anchor Bars: 500'/carton
Zinc Nail-In Anchor	Zinc-plated steel pin attaches termination bar to concrete or masonry walls.	X		Structural Concrete Masonry Wall	Grey	¼" (6 mm) dia., 1¼" (32 mm) length	1,000/box
Multi-Purpose							
Fasteners							
All-Purpose Fasteners	#14 case-hardened steel insulation and membrane fastener with a #3 Phillips head.	X	X	Metal (18-24 ga.) Wood Structural Concrete	Grey	1¼" to 4" (3.2 cm to 10.2 cm) 5" to 11" (12.7 cm to 27.9 cm) 12" to 24" (30.5 cm to 61.0 cm)	1¼" to 4" - 1,000/pail 5" to 11" - 500/pail 12" to 24" - 250/box
JM Retrodriller Fastener	Roof Membrane and Insulation Fastener.	X		Metal Purlins (18-24 ga.)	Grey	4" to 10" (10.2 cm to 25.4 cm)	500/pail

*Galvalume is a registered trademark of BIEC International, Inc. and some of its licensed producers.

Product	Description	Systems		Deck	Color	Size	Packaging
		Single Ply	Bituminous				
Structural Concrete Deck Fasteners	Diamond point, nonthreaded carbon steel insulation and membrane fastener.	X	X	Structural Concrete	Black	2½" to 10" (6.4 mm to 25.4 mm) lengths	2½"-8" - 500/pail 9"-10" - 250/pail
Plates							
JM isoweld®	Insulation and Membrane Fastening Plate.	X		Metal (18-24 ga.) Metal Purlins (18-24 ga.) Wood Structural Concrete	TPO: Yellow PVC: Purple	3" (7.6 cm) round	500/pail
JM PVC Rhinoplate®	Coated Galvalume® insulation and PVC membrane fastening plate with recessed center and raised flat-bonding surface.	X		Metal (18-24 ga.) Wood Structural Concrete	Black	3" (7.6 cm) round	500/pail
JM TPO Rhinoplate®	Coated Galvalume®, TPO fastening plate with a recessed center and raised flat-bonding surface.	X		Metal (18-24 ga.) Metal Purlins (18-24 ga.) Wood Structural Concrete	Amber	3" (7.6 cm) round	500/pail
Fastener and Plate Systems							
Polymer Auger Fastener with Plates	Solid glass-reinforced nylon membrane and insulation fasteners.	X	X	Cementitious Wood Fiber Gypsum	Black (fasteners) Grey (plates)	Fastener lengths: 2½" (6.4 cm) to 7½" (19.1 cm) Plate: 2" (51 mm) round and 3" (76 mm) square	Fastener: 500/pail Plate: 1,000/pail
UltraLok™ Locking Impact Fastener and Plate	Galvanized-steel tube and Galvalume®-coated steel disc clamped to a wire-locking staple.	X	X	Cementitious Wood Fiber Lightweight Insulated Concrete Gypsum	Black (fasteners) Grey (plates)	Fastener lengths: 1.4" to 1.7" (3.6 cm to 4.32 cm) Plate: 2.7" (6.9 cm)	500/carton