

**Attic Protector**

*Blow-in Loose-fill Fiber Glass Insulation*

**This is Blow-in  
Loose-fill Insulation**



**Manufacturer**  
Johns Manville  
717 17<sup>th</sup> Street  
Denver, CO 80202  
1-303-978-2000  
www.specjm.com

**Performance Data**

R-Value	Minimum Installed Thickness	Settled Thickness	Bags Per 1,000 Sq. Ft.	Maximum Net Coverage* (sq.ft./bag)	Minimum Weight (lbs./sq.ft.)
To obtain an insulation resistance (R) of:	Installed insulation should not be less than:	Expected thickness after long-term settling:	Number of bags per 1000 sq. ft. should not be less than:	Contents of this bag should not cover more than:	Weight per sq. ft. of installed insulation should not be less than:
11	5.2"	5.1"	5.4	186	0.135
13	6.1"	6.0"	6.4	155	0.161
19	8.7"	8.5"	9.7	103	0.242
22	9.9"	9.8"	11.4	88	0.285
26	11.5"	11.4"	13.7	73	0.343
30	13.1"	13.0"	16.1	62	0.402
38	16.2"	16.1"	21.1	47	0.527
44	18.5"	18.3"	25.0	40	0.625
49	20.3"	20.2"	28.4	35	0.710
60	24.3"	24.1"	36.2	28	0.904

\* The manufacturer recommends that the insulation be installed at these minimum thicknesses and maximum coverages to provide the levels of insulation thermal resistance (R-value) shown

**Read This Before You Buy**

**What You Should Know About R-values**

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulating power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your fuel savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house, and your fuel use patterns and family size. If you buy too much insulation, it will cost you more than what you'll save on fuel.

To get the marked R-value, it is essential that this insulation be installed properly.

Data as shown are intended to be used as general guidelines only. The physical and chemical properties of Attic Protector Blow-in Loose-fill insulation listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the sales office nearest you for current information.