

Features and Components

Presto-Weld drip edge is a factory-fabricated coated metal edge system used to terminate at the perimeter of a PVC or TPO membrane. This edge comes with a factory applied, 8" wide PVC flashing strip or 6" wide TPO flashing strip of Johns Manville membrane to help save labor installation costs in the field. Presto-Weld is an economical solution for many conditions such as continuous edge drainage with or without a gutter condition.


Anchor Cleat: 12' (3.7 m) lengths, 22 gauge (0.79 mm) formed galvanized steel, preslotted fastener holes at 12" (30.48 cm) o.c.

Fasteners: 1 ¼" (32 mm) ring shank roofing nails, provided.

Fascia Cover: 12' (3.7 m) lengths, available in 24 ga. (0.6 mm) steel PVC or TPO coated with pre-slotted fastener holes at 6" o.c.

Finishes: Standard membrane colors available.

Accessories: Factory-fabricated corners, and special angles and extenders are also available.



Component

S
Specialty

Single Ply

Type

EM
Edge Metal

Face Height

3" (76.2 mm)

4" (102 mm)

6" (152 mm)

System Compatibility *This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.*

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
<i>Do not use in Multi-Ply systems</i>								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Energy and the Environment

Pre-Consumer Recycled Content	Contact Specialty Roofing Products at (800) 445-1500
Post-Consumer Recycled Content	

Peak Advantage® Guarantee Information

Covered under the JM Peak Advantage Guarantee when installed in a JM approved roofing system.

Codes and Approvals



- FM 285 approved for face heights listed
- Meets ANSI/SPRI "Wind Design Standard" at a pressure of 282 lb/ft² for face heights listed

Installation/Application

Refer to JM applicator guides or detail drawings for instructions.

Packaging and Dimensions

Anchor Cleat	12' (3.7m) lengths, 22 ga (0.79 mm) formed galvanized steel, pre-slotted holes at 12" o.c.
Fasteners	1 ¼" (32 mm) ring shank roofing nails
Fascia Cover	12' (3.7 m) lengths Steel gauge: 24 gauge (0.61 mm) Steel finishes: Available in the full range Johns Manville PVC and TPO colors
Producing Location	Waukesha, WI

Refer to the Safe Use Instructions and product label prior to using this product. The Safe Use Instructions are available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.