


### SCRIM FINGER CUTS

SET JM PMMA SCRIM FINGER FLASHING INTO BED OF JM PMMA RESIN. EXTENDED MIN. 2" INTO DRAIN BOWL AND COVER WITH ANOTHER LAYER OF RESIN. INSTALL SCRIM TARGET PATCH OVER FINGER FLASHING. SEE NOTE 4


12" X 12" MIN. TARGET PATCH OF JM PMMA MEMBRANE OVER FINGER SCRIM



### FINGER FLASHING SCRIM

**NOTES:**

1. REFER TO JOHNS MANVILLE WEBSITE ([www.jm.com](http://www.jm.com)) FOR MOST UP-TO-DATE INFORMATION.
2. PLEASE SEE JM PMMA FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.
3. ANY CARPENTRY OR METAL WORK SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
4. JM PMMA MEMBRANE FLASHING CONSISTS OF JM PMMA STANDARD RESIN, JM PMMA SCRIM, JM PMMA STANDARD RESIN. USE THE APPROPRIATE JM PMMA PRIMER DEPENDING ON TYPE OF SUBSTRATE.



## ROOF DRAIN

DRAWING NO.

**LB-DV-01**

NEW DETAIL

MEMBRANE TYPE:

JM PMMA OVER BITUMINOUS

MAXIMUM GUARANTEE TERM:

20 YEAR

ISSUE DATE

6-18-18

SCALE

N.T.S

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

