

COUNTERFLASHING (BY OTHERS), OVER WALL FLANGES, TYPICAL.

FACTORY SOLDERED METAL FLANGES AT TRANSITION

APPROVED CONTINUOUS WOOD CANT @ 15° (MIN)

FLASHING STRIPS OF ROOF MEMBRANE, TYP. @ EXPANSION JOINT FLANGE.

FACTORY SEWN AND SEALED BELLOWS AT BELLOWS TRANSITION.

EXPAND-O-FLASH (STYLE EJ) ELASTOMERIC BELLOWS, CLOSED CELL FOAM BACKER AND INTEGRAL 4" WIDE METAL FLANGES, TYPICAL

APPROVED CONTINUOUS WOOD CANT @ 15° (MIN)

MANUFACTURERS APPROVED ROOFING SYSTEM

## NOTES:

- FOR ADDITIONAL APPLICATION INFORMATION OR TECHNICAL SERVICE PLEASE CONTACT OUR EXPAND-O-FLASH TECHNICAL SERVICE AT 800-445-1500
- THIS JOHNS MANVILLE PRODUCT CAN BE INCLUDED IN THE JM PEAK ADVANTAGE GUARANTEE. PLEASE CONTACT A JM TECHNICAL SERVICES SPECIALIST AT 800-922-5922 FOR SPECIFIC ROOFING AND FLASHING REQUIREMENTS.
- THIS DRAWING IS FOR REPRESENTATION PURPOSES ONLY. CONSULT EXPAND-O-FLASH TECHNICAL SERVICE FOR DEVIATIONS FROM THE ABOVE DETAIL
- SEE EXPAND-O-FLASH CUT SHEET FOR BELLOWS SIZING AND REQUIRED MOUNTING HEIGHT (IF APPLICABLE)
- CONTACT JM EXPAND-O-FLASH TECHNICAL SERVICE FOR INSTALLATION INSTRUCTIONS.

## ROOF TO WALL TEE (STYLE EJ)

DRAWING NO.

PF-16

SCALE

NTS

ISSUE DATE

5/9/12

REV. NO.

---

CAD FILE:

EOF TRANSITION DETAILS.DWG

Johns Manville is a Manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

