

Product	Accessory Product	Description	ASTM	Size
Fibrated Aluminum Roof Coating		Protective and reflective coating for use over BUR, SBS, and APP membranes as well as approved substrates.	ASTM D2824, Type III	4.75 gal (17.9 L) pail
Asphalt Emulsion Roof Coating		Protective coating over BUR, SBS, and APP membranes as well as approved substrates.	ASTM D1227, Type II, Class 1	4.75 gal (17.9 L) pail
TopGard Base Coat		Acrylic-based, bleed blocker for use over hot asphalt, asphalt emulsions, and BUR, SBS, and APP membranes.		5 gal (18.9 L) pail 55 gal (208 L) drum 275 gal (1041 L) tote
TopGard 4000		Acrylic reflective top coat with an initial SRI of 104. Available in both white and tan.		5 gal (18.9 L) pail 55 gal (208 L) drum 275 gal (1041 L) tote
TopGard 5000		Acrylic, high solids, reflective top coat with an initial SRI of 104. Available in both white and tan.	ASTM D6083	5 gal (18.9 L) pail 55 gal (208 L) drum 275 gal (1041 L) tote
JM Coating Universal Base		Water-borne, epoxy coating used to create a smooth base layer for JM Coating applications. Prevents bleed through over asphaltic substrates.		5 gal (18.9 L) pail
JM Coating Acrylic		Acrylic, reflective top coat with an initial SRI of 110. Designed for use with BUR, SBS, APP, TPO, and PVC membranes.	ASTM D6083	5 gal (18.9 L) pail 55 gal (208 L) drum 275 gal (1041 L) tote
JM Coating Acrylic CR		Acrylic, reflective top coat with an initial SRI of 114. Designed for use with BUR, SBS, APP, TPO, and PVC membranes.	ASTM D6083	5 gal (18.9 L) pail 55 gal (208 L) drum 275 gal (1041 L) tote
JM Coating Silicone		Silicone, high solids (98%), reflective top coat with an initial SRI of 114. Designed for use with BUR, SBS, APP, TPO, and EPDM membranes.	ASTM D6694	5 gal (18.9 L) pail 55 gal (208 L) drum
JM Coating Repair Tape	X	Seals seams, flashings, and repair areas prior to application of JM Coating systems.		4" x 50', 12 rolls/box 6" x 50', 8 rolls/box
JM Coating Polyester Reinforcing Fabric	X	Stitch-bonded polyester for use in JM Coating systems. Designed for use around penetrations, curbs and seams, and to increase tear strength, puncture resistance, and crack-bridging of reinforced liquid applied membranes.		4" x 300' 6" x 300' 12" x 300'
JM Coating Acrylic Flashing	X	Brush/trowel grade acrylic patch for use with JM Coating Acrylic systems.	ASTM D1475 ASTM D2196 ASTM D2939	3.5 gal (13.2 L) pail
JM Coating Silicone Flashing	X	Mastic coating for repair applications with reinforcing fabric or to seal common flashing conditions.		2 gal (7.57 L) pail
JM Coating Single Ply Primer	X	Solvent-based adhesion promoter for use on aged single ply membranes prior to JM Coating Acrylic or JM Coating Silicone applications.		5 gal (18.9 L) pail