

The following table shows the weight per linear foot of Thermo-1200 for the purpose of estimating the load on pipe supports.

Nominal Size	Pounds Per Linear ft	Nominal Size	Pounds Per Linear ft	Nominal Size	Pounds Per Linear ft	Nominal Size	Pounds Per Linear ft
½x1	1	2½x2	5	6x3	11	15x3	20
½x1½	1	2½x2½	6	7x1½	5	16x1½	10
½x2	2	2½x3	8	7x2	7	16x2	13
½x2½	4	3x1	2	7x2½	10	16x2½	17
½x3	5	3x1½	3	7x3	13	16x3	21
¾x1	1	3x2	4	8x1½	6	17x1½	10
¾x1½	1	3x2½	6	8x2	8	17x2	14
¾x2	2	3x3	7	8x2½	11	17x2½	18
¾x2½	4	3½x1	3	8x3	14	17x3	22
¾x3	5	3½x1½	4	9x1½	6	18x1½	11
1x1	1	3½x2	5	9x2	10	18x2	15
1x1½	2	3½x2½	7	9x2½	12	18x2½	19
1x2	3	3½x3	9	9x3	15	18x3	23
1x2½	4	4x1	2	10x1½	7	19x1½	11
1x3	5	4x1½	4	10x2	10	19x2	16
1¼x1	1	4x2	5	10x2½	13	19x2½	20
1¼x1½	2	4x2½	7	10x3	16	19x3	24
1¼x2	3	4x3	9	11x1½	8	20x2	16
1¼x2½	4	4½x1	3	11x2	11	20x2½	21
1¼x3	5	4½x1½	5	11x2½	14	20x3	25
1½x1	1	4½x2	6	11x3	17	21x2	17
1½x1½	2	4½x2½	8	12x1½	9	21x2½	21
1½x2	4	4½x3	10	12x2	12	21x3	27
1½x2½	5	5x1	3	12x2½	15	22x2	18
1½x3	7	5x1½	4	12x3	18	22x2½	23
2x1	1	5x2	6	14x1½	9	22x3	28
2x1½	2	5x2½	8	14x2	12	23x2	19
2x2	4	5x3	10	14x2½	15	23x2½	24
2x2½	5	6x1	3	14x3	19	23x3	29
2x3	6	6x1½	5	15x1½	9	24x2	19
2½x1	2	6x2	7	15x2	13	24x2½	25
2½x1½	3	6x2½	9	15x2½	16	24x3	30

THERMO-1200™

CALCIUM SILICATE PIPE & BLOCK INSULATION

LINEAR FOOT CHART

QUALITY STATEMENT

Johns Manville Industrial Insulation Group products are designed, manufactured and tested to strict quality standards in our own facilities. This along with third party auditing is your assurance that this product delivers consistent high quality.

ISO 9000 CERTIFICATION

Thermo-1200 is manufactured and tested in our own facilities under implemented Quality Management Systems which are certified to be in accordance with ISO 9001 quality standards. This certification, along with regular, independent third-party auditing of our plant and records for compliance, is your assurance that this product consistently delivers high quality performance.

PRODUCT CERTIFICATION

When ordering material to comply with any government specification or any other listed specification, a statement of that fact must appear on the purchase order. Government regulations and other listed specifications require specific lot testing, and prohibit the certification of compliance after shipment has been made. There may be additional charges associated with specification compliance testing. Please refer to IND-CSP-3 for Certification Procedures and Charges. Call customer service for more information (1-800-866-3234).



717 17th St.
Denver, CO 80202
800-866-3234
www.jm.com/industrial

IND- 310 05-17 (Replaces 01-15)

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The physical and chemical properties of the Thermo-1200 listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Any references to numerical flame spread or smoke developed ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions. Check with the Regional Sales Office nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville thermal insulation and systems, visit www2.jm.com/terms-conditions or call (800)654-3103.

© 2017 Johns Manville all rights reserved