

HOMEOWNER \_\_\_\_\_ DATE \_\_\_\_\_

ADDRESS \_\_\_\_\_

CITY \_\_\_\_\_ STATE \_\_\_\_\_ ZIP \_\_\_\_\_

### BLOWING WOOL

	R-VALUE	THICKNESS	COVERAGE AREA	NUMBER OF BAGS USED
Ceilings		in.	sq. ft.	
		in.	sq. ft.	
Walls		in.	sq. ft.	
		in.	sq. ft.	
Floors		in.	sq. ft.	
		in.	sq. ft.	

### CLIMATE PRO CAVITY WALL (SIDEWALL) COVERAGE CHART

R-VALUE (hr•sq.ft.°F/BTU)	MINIMUM INSTALLED THICKNESS (in.)	DENSITY OF INSULATION (lbs./cubic ft.)	MAXIMUM COVERAGE (sq.ft./bag)	MINIMUM WEIGHT (lbs./sq.ft.)
To obtain an insulation resistance (R) of	Installed insulation should not be less than:	Installed insulation should not be less than:	Contents of this bag should not cover more than:	The weight per sq. ft. of installed insulation should not be less than:
15	3.50	1.5	69	0.44
24	5.50	1.5	44	0.69
31	7.25	1.5	33	0.91
40	9.25	1.5	26	1.16
16	3.50	2.0	51	0.58
25	5.50	2.0	33	0.92
32	7.25	2.0	25	1.21
41	9.25	2.0	19	1.54

*\*This is coverage of unframed areas. Framing correction based on 16"oc=9% framing; 24"oc=6% framing.*

INSULATION CONTRACTOR SIGNATURE \_\_\_\_\_ DATE \_\_\_\_\_

COMPANY \_\_\_\_\_ ADDRESS \_\_\_\_\_ PHONE \_\_\_\_\_

HOME BUILDER SIGNATURE \_\_\_\_\_ DATE \_\_\_\_\_

COMPANY \_\_\_\_\_ ADDRESS \_\_\_\_\_ PHONE \_\_\_\_\_