

Features and Components

Use: To thoroughly clean the release agent and dirt from JM TPO and JM EPDM membranes prior to applying primers or splice adhesives.

Type: One-part, organic solvent cleaning agent.

Color: Clear



Component

CL
Cleaner

Type

M
Membrane
Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	HW	HA	CA	HW	SA	MF
Compatible with the selected Multi-Ply systems above								

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Compatible with the selected Single Ply systems above										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Maximum VOC	>650 g/l ¹ (EPA Method 24)
Vapor Pressure at 20° C	16 mm HG

1. Exceeds limits in SCAQMD rule 1168

Physical Properties

Property	JM EPDM Splice Cleaner
Weight per Unit (approx.)	6.20 lb/gal (0.74 kg/l)
Viscosity	<50 cps
Benzene Content	<0.01% (max)

Precautions

Johns Manville Weathered Membrane Cleaner is a combustible material and should be shipped and stored away from open flames, heat or sources of ignition. Keep all pails tightly sealed while in storage. It should be used only in well-ventilated areas. It may cause eye, skin and respiratory irritation, and is harmful or fatal if swallowed. Avoid contact with skin. Use impervious clothing and rubber gloves to avoid prolonged or repeated contact with skin. Read the container label and follow all safety instructions.

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at www.jm.com/roofing. The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

Installation/Application



Natural Fiber Cloth

- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to the application instructions guidelines for proper utilization of this cleaner.

Packaging and Coverage

Container Size	5 gal (18.9 l) pail
Shipping Weight (approx.)	32 lb (14.5 kg)
Pails per Pallet	45
Pallets per Truck	22
Coverage Rate	Will vary depending on the amount of release agent, dirt and debris.

Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Clean, dry, indoor environment, out of direct sunlight, in the original unopened container.
Temperature Range	60°F – 80°F (16°C – 27°C) - Protect from freezing

Exposure Window

Johns Manville recommends using open containers within 48 hours of opening. Replace lid on can when not in use.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit www.jm.com/terms-conditions.