



**NOTES:**

1. REFER TO JOHNS MANVILLE WEBSITE ([www.jm.com](http://www.jm.com)) FOR MOST UP-TO-DATE INFORMATION.
2. MAINTAIN 2" MIN. CLEARANCE FROM PENETRATION TO EDGE OF METAL PAN.
3. ROUND FLANGE CORNERS ON METAL PAN.
4. PRIME INSIDE OF METAL PAN WITH PERMAFLASH PRIMER WHERE MBR FLASHING CEMENT WILL BE PLACED.
5. PENETRATION PANS ARE CONSIDERED MAINTENANCE ITEMS AND ARE NOT GUARANTEED BY JOHNS MANVILLE.
6. USE ASPHALT PRIMER ON FLANGES WHEN USING MBR UTILITY CEMENT. USE PERMAFLASH PRIMER ON FLANGES WHEN USING MBR FLASHING CEMENT.
7. ANY CARPENTRY, METAL WORK, OR MASONRY CONSTRUCTION SHOULD BE DESIGNED AND CONSTRUCTED IN ACCORDANCE WITH LOCAL CODE REQUIREMENTS AND/OR PROJECT SPECIFICATIONS. THESE COMPONENTS SHOULD BE REVIEWED AND APPROVED BY A LICENSED DESIGN PROFESSIONAL.
8. PLEASE SEE BITUMINOUS FLASHING SPECIFICATIONS FOR A FULL DESCRIPTION OF INSTALLATION INSTRUCTIONS AND REQUIREMENTS WHICH ARE CONSIDERED A PART OF THIS DETAIL.

DRAWING NO.

**DGE-16**

**ROOF PENETRATION PAN**

PENETRATION

MEMBRANE TYPE:  
BUR

SCALE  
N.T.S

ISSUE DATE  
12-12-18

MAXIMUM GUARANTEE TERM:

Johns Manville is a manufacturer of commercial roofing products and offers this general conceptual information to you as a courtesy. This complimentary assistance is not to be used or relied upon by anyone as a substitute for professional engineering design and documentation required by building code, contract, or applicable law. By accepting these comments you agree they do not constitute any representations, endorsements of, or an assumption by Johns Manville of any liability for either the adequacy of the design of this building or any other material not supplied by Johns Manville.

