

**Weather Protective Coating**

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : Insulkote® ET, INSULKOTE® ET

## Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127  
Telephone : +1-303-978-2000  
Emergency telephone : 24-Hour Number: +1-800-424-9300 (CHEMTREC)  
number

Company : Johns Manville Canada Inc.  
Address : 5301 42 Avenue  
Innisfail, AB Canada T4G 1A2  
Telephone : +1-303-978-2000  
Emergency telephone : 24-Hour Number: +1-800-424-9300 (CHEMTREC)  
number

## Recommended use of the chemical and restrictions on use

Restrictions on use : For professional users only.  
Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Not a hazardous substance or mixture.

**GHS label elements**

Not a hazardous substance or mixture.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

| Chemical name              | CAS-No.    | Concentration (%)  |
|----------------------------|------------|--------------------|
| asphalt                    | 8052-42-4  | $\geq 30$ - $< 60$ |
| limestone                  | 1317-65-3  | $\geq 1$ - $< 5$   |
| quartz (SiO <sub>2</sub> ) | 14808-60-7 | $\geq 0.1$ - $< 1$ |

Actual concentration or concentration range is withheld as a trade secret

**SECTION 4. FIRST AID MEASURES**

General advice : Handle in accordance with good industrial hygiene and safety practice.  
If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.

## Weather Protective Coating

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

|   |   |   |
|---|---|---|
| In case of skin contact                                     | : | In case of contact, flush skin with plenty of water for at least 5 minutes.<br>Call a physician if irritation develops or persists.   |
| In case of eye contact                                      | : | Rinse immediately with plenty of water, also under the eyelids, for at least 5 minutes.<br>If easy to do, remove contact lens, if worn.<br>Protect unharmed eye.<br>If eye irritation persists, consult a specialist.   |
| If swallowed  | : | DO NOT induce vomiting unless directed to do so by a physician or poison control center.<br>Gently wipe or rinse the inside of the mouth with water.<br>Never give anything by mouth to an unconscious person.<br>If symptoms persist, call a physician or Poison Control Centre immediately. |
| Most important symptoms and effects, both acute and delayed | : | None known.   |
| Protection of first-aiders                                  | : | If potential for exposure exists refer to Section 8 for specific personal protective equipment.   |

### SECTION 5. FIREFIGHTING MEASURES

|   |   |   |
|---|---|---|
| Suitable extinguishing media                  | : | Carbon dioxide (CO <sub>2</sub> )<br>Dry chemical<br>Foam<br>Water spray  |
| Unsuitable extinguishing media                | : | High volume water jet   |
| Specific hazards during firefighting          | : | Vapours may form flammable mixture with air   |
| Hazardous combustion products                 | : | carbon oxides<br>aluminum oxides<br>Silicon oxides  |
| Specific extinguishing methods                | : | Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.<br>Use water spray to cool unopened containers. |
| Special protective equipment for firefighters | : | In the event of fire, wear self-contained breathing apparatus.  |

### SECTION 6. ACCIDENTAL RELEASE MEASURES

|   |   |   |
|---|---|---|
| Personal precautions, protective equipment and emergency procedures | : | Evacuate personnel to safe areas.<br>Refer to protective measures listed in sections 7 and 8.   |
| Environmental precautions   | : | Prevent further leakage or spillage if safe to do so.<br>Clean contaminated floors and objects thoroughly while observing environmental regulations.<br>The product should not be allowed to enter drains, water courses or the soil. |
| Methods and materials for containment and cleaning up               | : | Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).<br>Keep in suitable, closed containers for disposal.   |

## Weather Protective Coating

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

### SECTION 7. HANDLING AND STORAGE

- Local/Total ventilation : Do not use in areas without adequate ventilation.
- Advice on protection against fire and explosion : Vapours may form explosive mixtures with air.  
Vapours are heavier than air and may spread along floors.
- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.
- Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.  
To maintain product quality, do not store in heat or direct sunlight.
- Materials to avoid : No materials to be especially mentioned.
- Recommended storage temperature : 10 - 49 °C
- Further information on storage stability : Keep in a dry, cool place.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

| Components                 | CAS-No.    | Value type<br>(Form of exposure) | Control parameters /<br>Permissible concentration  | Basis     |
|----------------------------|------------|----------------------------------|--|-----------|
| asphalt                    | 8052-42-4  | TWA (Fume, inhalable fraction)   | 0.5 mg/m <sup>3</sup><br>(benzene soluble aerosol) | ACGIH     |
|                            |            | C (Fumes)                        | 5 mg/m <sup>3</sup>                                | NIOSH REL |
| limestone                  | 1317-65-3  | TWA (total dust)                 | 15 mg/m <sup>3</sup>                               | OSHA      |
|                            |            | TWA (respirable fraction)        | 5 mg/m <sup>3</sup>                                | OSHA      |
|                            |            | TWA (respirable)                 | 5 mg/m <sup>3</sup><br>(Calcium carbonate)         | NIOSH REL |
|                            |            | TWA (total)                      | 10 mg/m <sup>3</sup><br>(Calcium carbonate)        | NIOSH REL |
| quartz (SiO <sub>2</sub> ) | 14808-60-7 | TWA (Respirable fraction)        | 0.025 mg/m <sup>3</sup>                            | ACGIH     |
|                            |            | TWA (respirable)                 | 10 mg/m <sup>3</sup> /<br>%SiO <sub>2</sub> +2     | OSHA      |
|                            |            | TWA (respirable)                 | 250 mppcf /<br>%SiO <sub>2</sub> +5                | OSHA      |
|                            |            | TWA (Respirable dust)            | 0.05 mg/m <sup>3</sup>                             | NIOSH REL |
|                            |            | TWA                              | 0.05 mg/m <sup>3</sup>                             | OSHA      |

## Weather Protective Coating

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

|  |  |                   |  |  |
|--|--|-------------------|--|--|
|  |  | (Respirable dust) |  |  |
|--|--|-------------------|--|--|

**Engineering measures** : Use a local and/or general ventilation system.  
Provide exhaust ventilation close to floor level.

**Personal protective equipment**

Respiratory protection : No personal respiratory protective equipment normally required.

Hand protection  
Material : Protective gloves

Remarks : Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

Eye protection : Wear safety glasses with side shields or goggles.

Skin and body protection : Wear protective clothing, such as long-sleeved shirts and pants.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.  
Written instructions for handling must be available at the work place.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste  
Colour : black  
Odour : mild, hydrocarbon-like  
Odour Threshold : No data available

pH : No data available  
Melting point/freezing point : No data available  
Initial boiling point and boiling range : 100 °C  
Flash point : 238 °C

Evaporation rate : 1  
(Water = 1.0)

Flammability (solid, gas) : No data available  
Upper explosion limit : No data available  
Lower explosion limit : No data available  
Vapour pressure : No data available  
Relative vapour density : 1(Air = 1.0)

Relative density : 1.038(Water = 1.0)

Solubility(ies)  
Water solubility : completely miscible

Solubility in other solvents : No data available  
Partition coefficient: n-octanol/water : No data available  
Auto-ignition temperature : No data available  
Thermal decomposition : No data available

**Weather Protective Coating**

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

Viscosity, dynamic : No data available  
Viscosity, kinematic : No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No dangerous reaction known under conditions of normal use.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : No hazards to be specially mentioned.  
Conditions to avoid : None known.  
Incompatible materials : No data available  
Hazardous decomposition products : In case of fire hazardous decomposition products may be produced such as:  
Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute dermal toxicity : Acute toxicity estimate : 4,545 mg/kg  
Method: Calculation method

**Acute toxicity****Components:****asphalt:**

Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat, male and female): > 0.0944 mg/l  
Exposure time: 4.5 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg  
Method: OECD Test Guideline 402

**Acute toxicity****limestone:**

Acute oral toxicity : LD0 (Rat, female): > 2,000 mg/kg  
Method: OECD Test Guideline 420

Acute inhalation toxicity : LC50 (Rat, male and female): > 3 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg

## Weather Protective Coating

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

Method: OECD Test Guideline 402

### Acute toxicity

#### quartz (SiO<sub>2</sub>):

Acute oral toxicity : LD50 (Rat): &gt; 22,500 mg/kg

Acute inhalation toxicity : Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : Assessment: The substance or mixture has no acute dermal toxicity

### IARC

Group 1: Carcinogenic to humans

quartz (SiO<sub>2</sub>) 14808-60-7

### OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and Hazardous Substances).

### NTP

Known to be human carcinogen

quartz (SiO<sub>2</sub>) 14808-60-7

## SECTION 12. ECOLOGICAL INFORMATION

### Ecotoxicity

#### Components:

#### quartz (SiO<sub>2</sub>):

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 10,000 mg/l  
Exposure time: 72 h

### Persistence and degradability

No data available

### Bioaccumulative potential

No data available

### Mobility in soil

No data available

### Other adverse effects

#### Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I Substances  
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

**Weather Protective Coating**

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

- Waste from residues : Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.  
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Packaging that cannot be reused after cleaning must be disposed or recycled in accordance with all federal, national and local regulations.

**SECTION 14. TRANSPORT INFORMATION****International transport regulations****Land transport**

USDOT: Not classified as a dangerous good under transport regulations

TDG: Not classified as a dangerous good under transport regulations

**Sea transport**

IMDG: Not classified as a dangerous good under transport regulations

**Air transport**

IATA/ICAO: Not classified as a dangerous good under transport regulations

**SECTION 15. REGULATORY INFORMATION****TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**Weather Protective Coating**

Version 3.0

Revision Date 03/31/2021

Print Date 03/31/2021

**SARA 313**

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.


**Clean Air Act**

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM Intermediate or Final VOC's (40 CFR 60.489).

**California Prop. 65**

 **WARNING:** This product can expose you to chemicals including chromium (hexavalent compounds), which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

TSCA : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

---

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date : 03/31/2021

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.