

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM Weathered Membrane Cleaner (TPO & EPDM)

Manufacturer or supplier's details

Company : Johns Manville
 Address : P.O. Box 5108
 Denver, CO USA 80127
 Telephone : +1-303-978-2000
 Emergency telephone : +1-800-424-9300 (CHEMTREC)
 number

Company : Johns Manville Canada Inc.
 Address : 5301 42 Avenue
 Innisfail, AB Canada T4G 1A2
 Telephone : +1-303-978-2000
 Emergency telephone : +1-800-424-9300 (CHEMTREC)
 number

Recommended use of the chemical and restrictions on use

Restrictions on use : For professional users only.

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)

Flammable liquids : Category 2
 Specific target organ toxicity : Category 3 (Respiratory system)
 - single exposure
 Skin irritation : Category 2
 Aspiration hazard : Category 1

GHS label elements

Hazard pictograms : 

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
 H304 May be fatal if swallowed and enters airways.
 H315 Causes skin irritation.
 H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

P210 Keep away from heat/sparks/open flames/hot surfaces.
 No smoking.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting
 equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P264 Wash skin thoroughly after handling.
 P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
 P271 Use only outdoors or in a well-ventilated area.
 P233 Keep container tightly closed.
 P280 Wear protective gloves/ protective clothing/ eye protection/
 face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON
 CENTER/doctor.
 P302 + P352 IF ON SKIN: Wash with plenty of water.
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately
 all contaminated clothing. Rinse skin with water/shower.
 P304 + P340 IF INHALED: Remove victim to fresh air and keep
 at rest in a position comfortable for breathing.
 P312 Call a POISON CENTER/doctor/.? if you feel unwell.
 P331 Do NOT induce vomiting.
 P332 + P313 If skin irritation occurs: Get medical advice/
 attention.
 P362 + P364 Take off contaminated clothing and wash it before
 reuse.
 P370 + P378 In case of fire: Use water spray, alcohol-resistant
 foam, dry chemical or carbon dioxide to extinguish.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container
 tightly closed.
 P235 Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in
 accordance with local, regional, national and international
 regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS
Hazardous components

Chemical name	CAS-No.	Concentration (%)
naptha, petroleum ether and petroleum distillates mixture	Not Assigned	>= 80 - <= 100
octane	111-65-9	>= 5 - <= 10
heptane	142-82-5	>= 5 - <= 10

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.
- If inhaled : If inhaled, remove to fresh air.
If not breathing, give artificial respiration.
If unconscious, place in recovery position and seek medical advice.
Consult a physician after significant exposure.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
If skin irritation persists, call a physician.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
Keep eye wide open while rinsing.
Remove contact lenses.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : Do NOT induce vomiting.
Rinse mouth with water.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Irritation
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Carbon dioxide (CO₂)
Dry chemical
Halons
Foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon oxides
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
For safety reasons in case of fire, cans should be stored separately in closed containments.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Evacuate personnel to safe areas.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours).
Use only explosion-proof equipment.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.
Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Take precautionary measures against static discharges.
Provide sufficient air exchange and/or exhaust in work rooms.
Open drum carefully as content may be under pressure.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : No smoking.
Keep container tightly closed in a dry and well-ventilated place.

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Observe label precautions.

Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : Stable at normal ambient temperature and pressure.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
naphtha (petroleum), hydrotreated light	64742-49-0	TWA	500 ppm 2,000 mg/m ³	OSHA
solvent naphtha (petroleum), light aliph.	64742-89-8	TWA	500 ppm 2,000 mg/m ³	OSHA
Distillates (petroleum), light distillate hydrotreating process, low-boiling	68410-97-9	TWA	500 ppm 2,000 mg/m ³	OSHA
octane	111-65-9	TWA	75 ppm 350 mg/m ³	NIOSH REL
		C	385 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,350 mg/m ³	OSHA
		TWA	300 ppm 1,450 mg/m ³	OSHA
		STEL	375 ppm 1,800 mg/m ³	OSHA
		TWA	300 ppm	ACGIH
heptane	142-82-5	TWA	85 ppm 350 mg/m ³	NIOSH REL
		C	440 ppm 1,800 mg/m ³	NIOSH REL
		TWA	500 ppm 2,000 mg/m ³	OSHA
		TWA	400 ppm 1,600 mg/m ³	OSHA
		STEL	500 ppm 2,000 mg/m ³	OSHA
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection Material	:	Impervious gloves
Remarks	:	Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).
Eye protection	:	Tightly fitting safety goggles Safety glasses
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday. Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Color	:	colourless
Odor	:	hydrocarbon-like
Odor Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	117.78 - 150 °C
Flash point	:	13.89 - 20.5 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	No data available

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

Lower explosion limit	: Not applicable
Vapour pressure	: No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.91 g/cm ³
Solubility(ies)	
Water solubility	: 0.05 g/l negligible
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: > 1,100,000 mPa.s
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity****Components:****octane:**

Acute inhalation toxicity : LC50 (Rat): 118,000 mg/l
Exposure time: 4 h

Acute toxicity**heptane:**

Acute oral toxicity : LD50 (Rat): > 15,000 mg/kg

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

Acute inhalation toxicity : LC50 (Rat): 103 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Skin corrosion/irritation**Product:**

Remarks: May cause skin irritation in susceptible persons.

Skin corrosion/irritation**Components:****heptane:**

Result: Skin irritation

IARC

Group 2B: Possibly carcinogenic to humans

naptha, petroleum ether and
petroleum distillates mixture

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

STOT - single exposure**Components:****octane:**

Assessment: May cause drowsiness or dizziness.

STOT - single exposure**heptane:**

Assessment: May cause drowsiness or dizziness.

Components:**heptane:**

Repeated dose toxicity - : Causes skin irritation.
Assessment

Aspiration toxicity**Components:****octane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

heptane:

May be fatal if swallowed and enters airways.

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity**

No data available

Persistence and degradability

No data available

Bioaccumulative potential**Components:****octane:**Partition coefficient: n-
octanol/water : log Pow: 5.15**Mobility in soil**

No data available

Other adverse effects**Product:**Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances
Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).Additional ecological
information : No data available**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**Disposal of residual product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with
chemical or used container.
Dispose of contents/container to an approved facility in
accordance with local, regional, national and international
regulations.Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.**SECTION 14. TRANSPORT INFORMATION**

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

International transport regulations

US DOT: UN1268, Petroleum distillates, n.o.s., 3, II

SECTION 15. REGULATORY INFORMATION
TSCA list

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Specific target organ toxicity (single or repeated exposure)
 Skin corrosion or irritation
 Aspiration hazard

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.


SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489).

California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)
 **WARNING:** This product can expose you to chemicals including benzene, which is/are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL : All components of this product are on the Canadian DSL

TSCA : On the inventory, or in compliance with the inventory

JM Weathered Membrane Cleaner (TPO & EPDM)

Version 2.0

Revision Date 06/25/2019

Print Date 06/25/2019

SECTION 16. OTHER INFORMATION**Further information**

Revision Date : 06/25/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.