

JM Climate Pro® Fiber Glass Blowing Wool

Your home has been professionally insulated with a premium installation system.

(The higher the R-value, the greater the insulating power.)

Homeowner's Name _____ Date _____

Address _____

City _____ State _____ Zip _____

BLOWING WOOL

	R-VALUE	THICKNESS	COVERAGE AREA	NUMBER OF BAGS USED
Ceilings		in.	sq. ft.	
		in.	sq. ft.	
Walls		in.	sq. ft.	
		in.	sq. ft.	
Floors		in.	sq. ft.	
		in.	sq. ft.	

CLIMATE PRO PREMIUM FIBER GLASS BLOWING WOOL INSULATION COVERAGE CHART FOR CLIMATE PRO INSULATION USED FOR THE BLOW-IN BLANKET SYSTEM® AND CLOSED CAVITIES

R-VALUE	CAVITY DEPTH/INSULATION THICKNESS	DENSITY	MINIMUM WEIGHT PER SQ. FT.	MAXIMUM COVERAGE PER BAG*
	INCHES	POUNDS PER CUBIC FOOT	POUNDS PER SQ. FT.	SQ. FT. PER BAG
15	3.50	1.5	0.44	72.0
23	5.50	1.5	0.69	45.8
30	7.25	1.5	0.91	34.8
38	9.25	1.5	1.16	27.2
16	3.50	2.0	0.58	54.0
24	5.50	2.0	0.92	34.4
31	7.25	2.0	1.21	26.1
39	9.25	2.0	1.54	20.4

*This is coverage of unframed areas.

Framing correction based on 16"oc=9% framing; 24"oc=6% framing.

R-VALUE	DENSITY	MAXIMUM COVERAGE WITH FRAMING 93" HIGH CAVITY SQ. FT. PER BAG		MAXIMUM COVERAGE WITH FRAMING 93" HIGH CAVITY LINEAL FEET PER BAG		MAXIMUM COVERAGE WITH FRAMING 93" HIGH CAVITY CAVITIES PER BAG	
		16" CENTERS	24" CENTERS	16" CENTERS	24" CENTERS	16" CENTERS	24" CENTERS
15	1.5	79.4	76.8	10.3	9.9	7.7	5.0
23	1.5	50.6	48.9	6.5	6.3	4.9	3.2
30	1.5	38.4	37.1	4.9	4.8	3.7	2.4
38	1.5	30.1	29.1	3.9	3.7	2.9	1.9
16	2.0	59.6	57.6	7.7	7.4	5.8	3.7
24	2.0	37.9	36.7	4.9	4.7	3.7	2.4
31	2.0	28.8	27.8	3.7	3.6	2.8	1.8
39	2.0	22.5	21.8	2.9	2.8	2.2	1.4

Insulation Contractor Signature _____ Date _____

Company _____ Address _____ Phone _____

Home Builder Signature _____ Date _____

Company _____ Address _____ Phone _____





THIS IS FIBER GLASS BLOWING WOOL INSULATION

JM CLIMATE PRO® FIBER GLASS BLOWING WOOL INSULATION, BIBS® APPLICATION

R-VALUE	CAVITY DEPTH/INSULATION THICKNESS	DENSITY	MINIMUM WEIGHT PER SQ. FT.	MAXIMUM COVERAGE PER BAG
	INCHES	POUNDS PER CUBIC FOOT	POUNDS PER SQ. FT.	SQ. FT. PER BAG
15	3.50	1.5	0.44	72.0
23	5.50	1.5	0.69	45.8
30	7.25	1.5	0.91	34.8
38	9.25	1.5	1.16	27.2
16	3.50	2.0	0.58	54.0
24	5.50	2.0	0.92	34.4
31	7.25	2.0	1.21	26.1
39	9.25	2.0	1.54	20.4

READ THIS BEFORE YOU BUY

What you should know about R-values:

The chart shows the R-value of this insulation. R means resistance to heat flow. The higher the R-value, the greater the insulation power. Compare insulation R-values before you buy.

There are other factors to consider. The amount of insulation you need depends mainly on the climate you live in. Also, your energy savings from insulation will depend upon the climate, the type and size of your house, the amount of insulation already in your house and your energy-use patterns and family size.

To get the marked R-value, it is essential that this insulation be installed properly with pneumatic equipment.

