

JM Climate Pro® A2000 Fiber Glass Blowing Wool

Your home has been professionally insulated with a premium installation system.

(The higher the R-value, the greater the insulating power.)

Homeowner's Name _____ Date _____

Address _____

City _____ State _____ ZIP _____

BLOWING WOOL

	R-VALUE	THICKNESS	COVERAGE AREA	NUMBER OF BAGS USED
Ceilings		in.	sq. ft.	
		in.	sq. ft.	
Walls		in.	sq. ft.	
		in.	sq. ft.	
Floors		in.	sq. ft.	
		in.	sq. ft.	

CLIMATE PRO A2000 PREMIUM FIBER GLASS BLOWING WOOL INSULATION COVERAGE CHART FOR CLIMATE PRO A2000 INSULATION USED FOR THE BLOW-IN-BLANKET® SYSTEM AND CLOSED CAVITIES

R-VALUE (HR•SQ.FT.°F/BTU)	CAVITY DEPTH/INSULATION THICKNESS INCHES	DENSITY POUNDS PER CUBIC FOOT	MAXIMUM COVERAGE PER BAG* (SQ.FT./BAG)	MINIMUM WEIGHT PER UNIT AREA (POUNDS/SQ.FT.)
15	3.50	2.0	50.6	0.58
23	5.50	2.0	32.2	0.92
31	7.25	2.0	24.4	1.21
39	9.25	2.0	19.1	1.54

*This is coverage of unframed areas.

Insulation Contractor Signature _____ Date _____

Company _____ Address _____ Phone _____

Home Builder Signature _____ Date _____

Company _____ Address _____ Phone _____



Visit our website at www.JM.com or call 1-800-654-3103 | Building Insulation Division P.O. Box 5108 | Denver, CO 80217-5108