

## Features and Components

**Use:** For field seaming JM EPDM membranes. Utilizes a clear polyethylene release liner for ease of installation.

**Materials:** 3" or 6" (7.62 cm or 15.24 cm) wide, self-adhering, extruded EPDM (ethylene propylene diene monomer) with a clear polyethylene release liner.

**Color:** Black



**Component**

**A**  
Accessory  
Single Ply

**Type**  
**MS**  
Membrane Seaming

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR			APP			SBS		
	HA	CA	HW	HA	CA	HW	SA	MF	
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
<i>Compatible with the selected Single Ply systems above</i>										

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

## Installation/Application



Self-Adhered

- Prime EPDM membrane with JM Tape Primer or JM Tape Primer (Low VOC) before applying to JM EPDM Seam Tape Plus.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

## Packaging and Dimensions

Roll Sizes	3" x 100' (7.62 cm x 30.48 m)	6" x 100' (15.24 cm x 30.48 m)
Thickness	0.030" (0.76 mm)	
Roll Coverage	25 ft <sup>2</sup> (2.33 m <sup>2</sup> )	50 ft <sup>2</sup> (4.65 m <sup>2</sup> )
Rolls per Box*	4	2
Linear Units per Box	400 lin ft (121.92 lin m)	200 lin ft (60.96 lin m)
Weight per Box	24 lb (10.89 kg)	25 lb (11.34 kg)

\*Each box of JM EPDM Seam Tape Plus includes scrubber pads and handle for seam priming.

## Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
Temperature Range	60°F – 80°F (16°C – 27°C)