

Features and Components

- Use:** Specifically designed for round, roof penetrations eliminating the need for field-fabrication. The large double-thick molded ribs, at the top of each step, offer superior tear resistance as well as a cutting guide.
- Materials:** Uncured EPDM (ethylene propylene diene monomer) with a pressure sensitive seam tape around the bottom.
- Color:** Black



Component

A
Accessory

Single Ply

Type

FP
Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Physical Properties of the Butyl Tape*

Property	JM EPDM Peel & Stick Pipe Boots
Weight per ft ²	0.29 lb/ft ² (1.4 kg/m ²)
Tensile Strength	75 psi (517 kPa)
Elongation	800 - 1200%
Peel Strength @ 70°F [21°C]	8 - 10 pli (1.43 - 1.79 kg/cm)
Shear Strength @ 70°F [21°C]	35 - 45 psi (241 - 310 kPa)

*The cured JM EPDM Peel & Stick Pipe Boots meet or exceed the requirements of ASTM D 4811.

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

- Prime EPDM membrane with JM Tape Primer or JM Tape Primer (Low VOC) before applying JM EPDM Peel & Stick Pipe Boots.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

Packaging and Dimensions

Sizes	1" - 6" (2.54 cm - 15.24 cm)
Thickness: Membrane	0.060" (1.52 mm)
Tape	0.030" (0.76 mm)
Total	0.090" (2.28 mm)
Boots per Box	10 (clamping rings included)
Weight per Box	15 lb (6.8 kg)

Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, keep clean and dry prior to use.
Temperature Range	60°F – 80°F (16°C – 27°C)