

Features and Components

Use: JM 3 oz Polyester Slipsheet is intended for use as a separation layer between an existing roof system and a new single ply recover system.

Material: 3.0 oz/yd² (102 g/m²) needle-punched, non UV-resistant polyester fabric.

Color: White



Component

A
Accessory

Single Ply

Type

PT
Protection

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
Do not use in Multi-Ply systems								

Single Ply	TPO		PVC		EPDM		
	MF	AD	MF	AD	MF	AD	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened AD = Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in mechanically fastened single ply recover and EPDM ballasted applications over existing smooth bituminous and single ply membranes.*

*Contact JM Technical Services @ 800-922-5922 opt. 3 for further information and qualifying guarantee assemblies and terms.

Installation/Application



Loose Laid

- JM 3 oz Polyester Slipsheet is installed between the existing roof and single ply membrane.
- JM 3 oz Polyester Slipsheet must be installed with a 3" minimum side lap and a 6" minimum end lap. Sheet may be tacked into place as deemed necessary.

Packaging and Dimensions

Roll Size	130" wide x 500' long (3.3 m x 152.4 m)
Coverage per Roll	5,416 ft ² (503 m ²)
Weight per Roll	150 lb (68.0 kg)

Storage

Storage Conditions	Store indoors, out of direct sunlight, in a cool, dry location prior to application.
--------------------	--