

Features and Components

- Use:** Provides a visual and physical safety warning on roof top areas of caution and potential hazards including designation of the roof perimeter.
- Material:** 55 mil (1.40 mm) total thickness, comprised of 30 mil (0.76 mm) yellow non-reinforced TPO membrane laminated to 25 mil (0.64 mm) white cured seaming tape.
- Colors:** Yellow



Component
A Accessory
Single Ply
Type
PT Protection

System Compatibility

This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
<i>Compatible with the selected Single Ply systems above</i>										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and Environment

LEED®	Recycled Content: Post-consumer: 0% Post-industrial: 0%
-------	---

Physical Properties

Property	JM TPO Safety Strip
Weight per Unit	0.52 lb/ft ² (2.54 kg/m ²)

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

When installing JM Single Ply Safety Strip be sure to:

- Minimize installing over seams and membrane splices whenever possible.
- Refer to JM TPO and EPDM applicator guides or detail drawings for instructions.

For installation over TPO membranes:

- Prime with JM TPO Membrane Primer or JM Single Ply Membrane Primer (Low VOC) according to their application instructions to prepare the membrane for the safety strip.

For installation over EPDM membranes:

- Prime with JM EPDM Tape Primer Plus or JM Single Ply Membrane Primer (Low VOC) according to their application instructions to prepare the membrane for safety strip.

Packaging and Dimensions

Roll Size	5.5' x 100' (14 cm x 30.48 m)
Thickness	55 mil (1.40 mm)
Rolls per Box	1
Weight per Roll	19 lb (8.6 kg)

Storage

Shelf Life	18 months when stored under appropriate conditions. If stored in non-optimal conditions shelf life may be reduced.
Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
Temperature Range	Store between 60 – 80 °F (15.6 – 26.7 °C)

Refer to the Safe Use Instructions and product label prior to using this product. The Safe Use Instructions are available by calling (800) 922-5922 or on the Web at www.jm.com/roofing.