

## Features and Components

**Use:** To secure the field membrane at any angle change greater than 2 in/ft (167 mm/m). JM TPO 6" RTS can be used in lieu of fastening through the field membrane with screws and plates at angle changes.

**Materials:** 45 mil (1.14 mm) thick reinforced TPO (thermoplastic polyolefin) membrane with 30 mil (0.76 mm) thick, factory-applied peel and stick adhesive tape.

**Color:** White



**Component**

**A**  
Accessory

Single Ply

**Type**

**PR**  
Perimeter Reinforcement

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
<b>Do not use with Multi-Ply systems</b>								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<b>Compatible with the selected Single Ply systems above</b>							

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

## Installation/Application



Self-Adhered



Mechanically Fastened

- This product must be both self-adhered and mechanically fastened to properly function.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM TPO applicator guides or detail drawings for instructions.

## Packaging and Dimensions

Roll Size	6" x 100' (15.2 cm x 30.48 m)
Thickness:	
Membrane	0.045" (1.14 mm)
Tape	0.030" (0.76 mm)
Total	0.075" (1.90 mm)
Coverage	50 ft <sup>2</sup> (4.65 m <sup>2</sup> )
Linear ft (m) per Roll	100 (30.48)
Rolls per Box	2

## Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, in original unopened containers
Temperature Range	60°F – 80°F (16°C – 27°C)