

Features and Components

Use: In lieu of half sheets to secure the roof membrane attachment beneath TPO or EPDM membrane and as additional membrane securement as specified in Johns Manville specifications and details.

Materials: 45 mil (1.14 mm) thick reinforced TPO (thermoplastic polyolefin) membrane with 30 mil (0.76 mm) thick, factory-applied peel and stick adhesive tape.

Color: White



Component

A
Accessory

Single Ply

Type

PR
Perimeter Reinforcement

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
Do not use with Multi-Ply systems								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered



Mechanically Fastened

- This product must be both self-adhered and mechanically fastened to properly function.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Size	10" x 100' (25.4 cm x 30.48 m)
Thickness:	
Membrane	0.045" (1.14 mm)
Tape	0.030" (0.76 mm)
Total	0.075" (1.90 mm)
Coverage	83.3 ft ² (7.74 m ²)
Linear ft (m) per Roll	100 (30.48)
Rolls per Box	1

Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, in original unopened containers
Temperature Range	60°F – 80°F (16°C – 27°C)