

## Features and Components

- Use:** To seal uneven penetrations through the membrane that are difficult to flash.
- Materials:** Uncured EPDM (ethylene propylene diene monomer) with a pressure sensitive seam tape around the bottom.
- Color:** Black



**Component**

**A**  
Accessory

Single Ply

**Type**

**FP**  
Penetration

## System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
<b>Do not use in multi-ply systems</b>									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
<b>Compatible with the selected single ply systems above</b>										

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

## Physical Properties of the Butyl Tape\*

Property	JM EPDM Peel & Stick Pourable Sealer Pockets
Tensile Strength	100 psi (690 kPa)
Peel Strength @ 70°F [21°C]	8 - 10 pli (1.43 - 1.79 kg/cm)
Shear Strength @ 70°F [21°C]	35 - 45 psi (241 - 310 kPa)

\* The cured JM EPDM Peel & Stick Pourable Sealer Pockets meet or exceed the requirements of ASTM D 4811.

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at [www.jm.com/roofing](http://www.jm.com/roofing). The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit [www.jm.com/terms-conditions](http://www.jm.com/terms-conditions).

## Installation/Application



Self-Adhered

- Prime EPDM membrane with JM Tape Primer or JM Tape Primer (Low VOC) before applying JM EPDM Peel & Stick Pourable Sealer Pockets.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

## Packaging and Dimensions

Size	6" (15.2 cm) diameter
Thickness: Membrane	0.060" (1.52 mm)
Tape	0.030" (0.76 mm)
Total	0.090" (2.28 mm)
Pockets per Box	12
Weight per Box	9.2 lb (4.2 kg)

## Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, keep clean and dry prior to use.
Temperature Range	60°F – 80°F (16°C – 27°C)