

Features and Components

Use: Primarily use to "strip-in" flashing details, gravel stops, PVC-Coated Metal joints, and exposed fasteners in the roof field.

Material: 60 mil (1.52 mm) thick, reinforced, UV-resistant PVC (polyvinyl chloride) with Elvaloy®* KEE (ketone ethylene ester).

Colors: 6" - Black/White
8" - White/Grey and Sandstone/White

* Elvaloy is a registered trademark of Dow.



Component

A
Accessory

Single Ply

Type

MS
Membrane
Seaming

FE
Flashing Edge

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

- Do not install JM PVC Detail Strip in direct contact with asphalt or coal tar pitch
- Refer to JM PVC applicator guides or detail drawings for instructions

Packaging and Dimensions

Roll Sizes	6" x 150' (15.2 cm x 45.7 m)	8" x 150' (20.3 cm x 45.7 m)
Nominal Thickness	0.060" (1.52 mm)	
Coverage per Roll	75 ft ² (6.97 m ²)	100 ft ² (9.29 m ²)
Weight per Roll	30 lb (13.6 kg)	40 lb (18.1 kg)

Storage

Storage Conditions	Store indoors, out of direct sunlight, in a cool, dry location prior to application.
--------------------	--