

Features and Components

Use: To seal seam laps where perimeter and/or header sheets intersect (T-joint) in TPO systems.

Material: Flexible, non-reinforced TPO (thermoplastic polyolefin).

Colors: White; Grey; and Tan



Component

A

Accessory

Single Ply

Type

MS
Membrane
Seaming

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

| Multi-Ply | BUR | | APP | | SBS | | | |
|--|-----|----|-----|----|-----|----|----|----|
| | HA | CA | CA | HW | HA | CA | HW | SA |
| <i>Do not use in Multi-Ply systems</i> | | | | | | | | |

| Single Ply | TPO | | PVC | | EPDM | | |
|--|-----|----|-----|----|------|----|----|
| | MF | AD | MF | AD | MF | AD | BA |
| <i>Compatible with the selected Single Ply systems above</i> | | | | | | | |

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened AD = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

| |
|--|
| Systems |
| Approved for use in any JM Peak Advantage Guarantee System |

Installation/Application



Hot Air Weld

- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

| | |
|-----------------|--------------------------|
| Size | 4.5" (11.43 cm) diameter |
| Patches per Box | 100 |
| Weight per Box | 3.2 lb (1.5 kg) |
| Thickness | 0.060" (1.52 mm) |

Storage

| | |
|--------------------|---|
| Storage Conditions | Store indoors, out of direct sunlight, and keep clean and dry prior to application. |
|--------------------|---|