

## Features and Components

**Use:** Used to seal uneven penetrations through the membrane that are difficult to flash. The penetration pan is comprised of two pieces that allow for positioning around objects to be flashed. A welding tab is included to seal the penetration pan once positioned.

**Material:** Two-piece molded TPO (thermoplastic polyolefin) pocket with a rigid vertical wall and preformed flange.

**Color:** White



**Component**

**A**

Accessory

Single Ply

**Type**

**FP**

Penetration

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

| Multi-Ply                                | BUR |    | APP |    | SBS |    |    |    |
|--|-----|----|-----|----|-----|----|----|----|
|  | HA  | CA | CA  | HW | HA  | CA | HW | SA |
| <b>Do not use with Multi-Ply systems</b> |     |    |     |    |     |    |    |    |

| Single Ply   | TPO |    | PVC |    | EPDM |    |    |
|--|-----|----|-----|----|------|----|----|
|  | MF  | FA | MF  | FA | MF   | FA | BA |
| <b>Compatible with the selected Single Ply systems above</b> |     |    |     |    |      |    |    |

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

## Peak Advantage® Guarantee Information

| Systems  |
|--|
| Approved for use in any JM Peak Advantage Guarantee System |

## Installation/Application



Hot Air Weld

Refer to JM TPO applicator guides or detail drawings for instructions.

## Packaging and Dimensions

|                   |                                |
|-------------------|--------------------------------|
| Size              | 7.5" x 6" (19 cm x 15 cm) Oval |
| Nominal Thickness | 0.156" (3.97 mm)               |
| Pockets per Box   | 5                              |

## Storage

|                    |   |
|--------------------|---|
| Storage Conditions | Store indoors, out of direct sunlight, and keep clean and dry prior to application. |
|--------------------|---|