
















ASTM		Product	Use					Reinforcement			Application					Roll Coverage*	Roll Weight
			Base	Ply	Cap	Flashing	Protection	Fiber Glass	Polyester	Composite	Hot Asphalt 	Cold Adhesive 	Heat Weld 	Self-Adhering 	Mechanically Fastened 		
D 6163	Type I, Grade S	DynaBase®	X					X			X	X				148.2 ft² (13.8 m²)	83 lb (38 kg)
		DynaBase® HW	X	X					X				X			148.2 ft² (13.8 m²)	83 lb (38 kg)
		DynaWeld™ Base	X	X		X			X				X			95.8 ft² (8.9 m²)	84 lb (38 kg)
	Type I, Grade G	JM CleanBond® Cap			X				X					X		95.8 ft² (8.9 m²)	107 lb (49 kg)
		DynaWeld™ Cap FR			X	X			X				X			95.8 ft² (8.9 m²)	106 lb (48 kg)
		DynaWeld™ Cap FR CR G			X	X			X				X			95.8 ft² (8.9 m²)	105 lb (47.6 kg)
		DynaWeld™ Cap			X	X			X				X			95.8 ft² (8.9 m²)	106 lb (48 kg)
		DynaGlas®			X				X		X	X				95.8 ft² (8.9 m²)	102 lb (46.3 kg)
		DynaGlas® 30 FR			X				X		X	X				95.8 ft² (8.9 m²)	95 lb (43.1 kg)
		DynaGlas® FR			X				X		X	X				95.8 ft² (8.9 m²)	102 lb (46 kg)
DynaGlas® FR CR G			X	X			X		X	X				95.8 ft² (8.9 m²)	96 lb (43.5 kg)		
D 6164	Type I, Grade S	DynaFast® 180 HW	X	X					X				X		X	148 ft² (14 m²)	100 lb (45.4 kg)
		DynaFast® 180 S	X	X					X		X	X			X	148 ft² (14 m²)	106 lb (48.1 kg)
		DynaBase® PR	X	X					X		X	X			X	148.2 ft² (13.8 m²)	85 lb (38.6 kg)
		DynaLastic® 180 S	X	X					X		X	X			X	95.8 ft² (8.9 m²)	86 lb (39 kg)
		DynaWeld™ 180 S	X	X					X				X			95.8 ft² (8.9 m²)	86 lb (39 kg)
		DynaGrip® Base PR SD/SA	X						X					X		148.2 ft² (13.8 m²)	95 lb (43.1 kg)
	Type I, Grade G	DynaLastic® 180			X	X			X		X	X				95.8 ft² (8.9 m²)	101 lb (46 kg)
		DynaLastic® 180 FR			X	X			X		X	X				95.8 ft² (8.9 m²)	101 lb (46 kg)
		DynaLastic® 180 FR CR G			X	X			X		X	X				95.8 ft² (8.9 m²)	96 lb (43.5 kg)
		DynaWeld™ Cap 180			X	X			X				X			95.8 ft² (8.9 m²)	105 lb (47.6 kg)
		DynaWeld™ Cap 180 FR			X	X			X				X			95.8 ft² (8.9 m²)	105 lb (47.6 kg)
		DynaWeld™ Cap 180 FR CR G			X	X			X				X			95.8 ft² (8.9 m²)	96 lb (43.5 kg)

*Roll Coverage assumes a 4" side lap.

ASTM		Product	Use					Reinforcement			Application					Roll Coverage*	Roll Weight
			Base	Ply	Cap	Flashing	Protection	Fiber Glass	Polyester	Composite	Hot Asphalt 	Cold Adhesive 	Heat Weld 	Self-Adhering 	Mechanically Fastened 		
D 6164	Type II, Grade S	DynaWeld™ 250 S	X	X		X			X				X			95.8 ft² (8.9 m²)	90 lb (40.8 kg)
		DynaLastic® 250 S	X	X		X			X		X	X				95.8 ft² (8.9 m²)	90 lb (40.8 kg)
		DynaFast® 250 HW	X	X					X				X		X	95.8 ft² (8.9 m²)	105 lb (47.6 kg)
	Type II, Grade G	DynaLastic® 250			X	X			X		X	X				95.8 ft² (8.9 m²)	115 lb (52.2 kg)
		DynaLastic® 250 FR			X	X			X		X	X				95.8 ft² (8.9 m²)	115 lb (52.2 kg)
		DynaLastic® 250 FR CR G			X	X			X		X	X				95.8 ft² (8.9 m²)	107 lb (48.5 kg)
		DynaWeld™ Cap 250			X	X			X				X			95.8 ft² (8.9 m²)	115 lb (52.2 kg)
DynaWeld™ Cap 250 FR			X	X			X				X			95.8 ft² (8.9 m²)	115 lb (52.2 kg)		
DynaWeld™ Cap 250 FR CR G			X	X			X				X			95.8 ft² (8.9 m²)	107 lb (48.5 kg)		
D 6162	Type I, Grade S	DynaPly® T1	X	X					X	X	X					95.8 ft² (8.9 m²)	87 lb (39.5 kg)
	Type I, Grade G	DynaKap® FR T1			X	X			X	X	X					95.8 ft² (8.9 m²)	105 lb (47.6 kg)
		DynaKap® FR T1 CR G			X	X			X	X	X					95.8 ft² (8.9 m²)	95 lb (43.1 kg)
		DynaKap® FR T1 HW			X	X			X				X			95.8 ft² (8.9 m²)	105 lb (47.6 kg)
		DynaKap® FR T1 HW CR G			X	X			X				X			95.8 ft² (8.9 m²)	100 lb (45.4 kg)
		DynaKap® T1			X	X			X	X	X					95.8 ft² (8.9 m²)	105 lb (47.63kg)
	Type III, Grade S	DynaMax™ FR S HW	X						X				X			95.8 ft² (8.9 m²)	95 lb (43.1 kg)
		DynaMax® FR Smooth	X						X	X	X					95.8 ft² (8.9 m²)	95 lb (43.1 kg)
	Type III, Grade G	DynaMax™ FR			X	X			X	X	X					95.8 ft² (8.9 m²)	105 lb (47.63kg)
		DynaMax™ FR CR G			X				X	X	X					95.8 ft² (8.9 m²)	105 lb (47.63 kg)
DynaMax™ FR HW				X	X			X				X			100 ft² (9.2 m²)	105 lb (47.63 kg)	

*Roll Coverage assumes a 4" side lap.

ASTM		Product	Use					Reinforcement			Application					Roll Coverage*	Roll Weight
			Base	Ply	Cap	Flashing	Protection	Fiber Glass	Polyester	Composite	Hot Asphalt 	Cold Adhesive 	Heat Weld 	Self-Adhering 	Mechanically Fastened 		
D 6162	Type III, Grade G	DynaMax™ FR HW CR G			X	X				X			X			100 ft² (9.2 m²)	105 lb (47.63 kg)
		DynaMax™ FR Plus			X	X					X	X				95.8 ft² (8.9 m²)	105 lb (47.63 kg)
		DynaMax™ FR Plus Smooth	X			X				X	X	X				95.8 ft² (8.9 m²)	95 lb (43.1 kg)
D 6221	Type I	DynaFlex®				X		X			X	X				75 ft² (6.9 m²)	81 lb (36.7 kg)
		DynaFlex® CR G				X		X			X	X				75 ft² (6.9 m²)	69 lb (31.3 kg)
D 6298		DynaClad®			X	X		X			X	X	X			95.8 ft² (8.9 m²)	100 lb (45.4 kg)
		DynaClad® Copper			X	X		X			X	X	X			95.8 ft² (8.9 m²)	100 lb (45.4 kg)
D 4601		DynaGrip® Base P/SA	X					X						X		194 ft² (18 m²)	90 lb (40.82kg)
		DynaGrip® Base SA/SA	X					X						X		194 ft² (18 m²)	80 lb (36.29 kg)
		DynaGrip® Base SD/SA	X					X						X		194 ft² (18 m²)	86 lb (39.1 kg)
		JM CleanBond® Base	X					X						X		200 ft² (18.5 m²)	88 lb (40 kg)
		DynaGrip® Base PR P/SA	X						X					X		148.2 ft² (13.8 m²)	90 lb (40.82kg)
		DynaGrip® Base PR SA/SA	X						X					X		148.2 ft² (13.8 m²)	90 lb (40.82 kg)
		DynaGrip® Base PR SD/SA	X						X					X		148.2 ft² (13.8 m²)	95 lb (43.10 kg)
		DynaGrip® Cap			X	X			X					X		95.8 ft² (8.9 m²)	96 lb (43.55 kg)
		DynaGrip® Cap PR			X	X			X					X		95.8 ft² (8.9 m²)	105 lb (47.63 kg)
		DynaTred™ Roof Walkway						X				X	X			7.11 ft² (0.66 m²)	
		DynaTred Plus® Roof Walkway						X				X	X			7.11 ft² (0.66 m²)	
D 4897	Type II	Ventsulation® Felt	X					X						X	100 ft² (9.3 m²)	68 lb (30.8 kg)	

*Roll Coverage assumes a 4" side lap.