

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : JM LVOC Membrane Adhesive (TPO &amp; EPDM)

Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127  
Telephone : +1 303-978-2000 8:00AM-5:00PM M-F  
Emergency telephone : 1-800-424-9300 (Chemtrec, in English)  
number

Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**Flammable liquids : Category 2  
Specific target organ toxicity : Category 3  
- single exposure  
Eye irritation : Category 2A  
Skin irritation : Category 3  
Specific target organ toxicity : Category 2  
- repeated exposure  
Reproductive toxicity : Category 2**GHS label elements**

Hazard pictograms



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H316 Causes mild skin irritation.  
H373 May cause damage to organs through prolonged or repeated exposure.  
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements

**Prevention:**P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting/  
equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P264 Wash skin thoroughly after handling.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.  
P271 Use only outdoors or in a well-ventilated area.  
P233 Keep container tightly closed.  
P280 Wear protective gloves/ protective clothing/ eye protection/  
face protection.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately  
all contaminated clothing. Rinse skin with water/shower.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water  
for several minutes. Remove contact lenses, if present and easy  
to do. Continue rinsing.  
P337 + P313 If eye irritation persists: Get medical advice/  
attention.  
P332 + P313 If skin irritation occurs: Get medical advice/  
attention.  
P370 + P378 In case of fire: Use dry sand, dry chemical or  
alcohol-resistant foam to extinguish.  
P304 + P340 IF INHALED: Remove victim to fresh air and keep  
at rest in a position comfortable for breathing.  
P314 Get medical advice/ attention if you feel unwell.  
P312 Call a POISON CENTER/doctor./?/if you feel unwell.  
P308 + P313 IF exposed or concerned: Get medical advice/  
attention.

**Storage:**

P403 + P233 Store in a well-ventilated place. Keep container  
tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**Disposal:**

P501 Dispose of contents/ container to an approved waste  
disposal plant.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

Chemical name	CAS-No.	Concentration (%)
tert-butyl acetate	540-88-5	>= 50 - < 70
acetone	67-64-1	>= 10 - < 20
toluene	108-88-3	>= 5 - < 10

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
Wash off with soap and water.  
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.  
Immediately flush eye(s) with plenty of water.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do NOT induce vomiting.  
Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : irritant effects

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray  
Halons  
Foam
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Carbon oxides
- Specific extinguishing methods : Standard procedure for chemical fires.  
Use a water spray to cool fully closed containers.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
For safety reasons in case of fire, cans should be stored separately in closed containments.  
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Evacuate personnel to safe areas.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

- Advice on protection against fire and explosion : Do not spray on a naked flame or any incandescent material.  
Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Prevent unauthorized access.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

kept upright to prevent leakage.  
 Observe label precautions.  
 Electrical installations / working materials must comply with  
 the technological safety standards.

**SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION**
**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
tert-butyl acetate	540-88-5	TWA	200 ppm	ACGIH
		TWA	200 ppm 950 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 950 mg/m <sup>3</sup>	OSHA
		TWA	200 ppm 950 mg/m <sup>3</sup>	OSHA
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA
		TWA	750 ppm 1,800 mg/m <sup>3</sup>	OSHA
		STEL	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA
		TWA	20 ppm	ACGIH
toluene	108-88-3	TWA	100 ppm 375 mg/m <sup>3</sup>	NIOSH REL
		ST	150 ppm 560 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm	OSHA
		CEIL	300 ppm	OSHA
		Peak	500 ppm (10 minutes)	OSHA
		TWA	100 ppm 375 mg/m <sup>3</sup>	OSHA
		STEL	150 ppm 560 mg/m <sup>3</sup>	OSHA

**Personal protective equipment**

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

Hand protection  
 Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

contact).

Eye protection	:	Tightly fitting safety goggles Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	:	Impervious clothing Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product. Written instructions for handling must be available at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	:	liquid
Colour	:	yellow
Odour	:	strong, sweet
Odour Threshold	:	No data available
pH	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	-4 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit	:	Not applicable
Lower explosion limit	:	Not applicable
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.91 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	not determined
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	1,500 - 3,500 mPa.s
Viscosity, kinematic	:	No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	None known.
Conditions to avoid	:	Heat, flames and sparks.
Incompatible materials	:	Strong oxidizing agents Acids and bases
Hazardous decomposition products	:	Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Nitrogen oxides (NOx)

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Components:****tert-butyl acetate:**

Acute oral toxicity	:	LD0 (Rat): 4,100 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 2.23 mg/l Exposure time: 4 h
Acute dermal toxicity	:	LD0 (Rabbit): 2 mg/kg

**Acute toxicity****acetone:**

Acute oral toxicity	:	LD50 (Rat, female): 5,800 mg/kg
Acute inhalation toxicity	:	LC50 (Rat): 120 mg/l Exposure time: 4 h Test atmosphere: vapour
Acute dermal toxicity	:	LD50 (Rabbit): 20,000 mg/kg

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

**Acute toxicity****toluene:**

Acute oral toxicity : LD50 Oral (Rat): 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit, male): &gt; 5,000 mg/kg

**Skin corrosion/irritation****Components:****toluene:**

Species: Rabbit

Assessment: Irritating to skin.

Result: Irritating to skin.

**Serious eye damage/eye irritation****Components:****acetone:**

Species: Rabbit

Result: Eye irritation

Exposure time: 24 h

Assessment: Irritating to eyes.

Method: Draize Test

**Serious eye damage/eye irritation****toluene:**

Species: Rabbit

Result: Mild eye irritation

Exposure time: 24 h

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Components:****toluene:**Reproductive toxicity -  
Assessment

: Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.



**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

**STOT - single exposure****Components:****acetone:**

Exposure routes: inhalation (vapour)

Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

**STOT - single exposure****toluene:**

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure****Components:****toluene:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Components:****toluene:**

May be fatal if swallowed and enters airways.

**Experience with human exposure****Components:****toluene:**

Skin contact:

Remarks:

Prolonged skin contact may defat the skin and produce dermatitis.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity**

No data available

**Persistence and degradability**

No data available

**Bioaccumulative potential****Components:****acetone:**Partition coefficient: n- : log Pow: 0.24  
octanol/water**toluene:**

Partition coefficient: n- : Pow: 2.7

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

octanol/water

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological information : No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Disposal of residual product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.  
Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

---

**SECTION 14. TRANSPORT INFORMATION****International transport regulations**

US DOT: UN1133, Adhesives, 3, II

---

**SECTION 15. REGULATORY INFORMATION****TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : Not relevant

US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D) : Not relevant

**EPCRA - Emergency Planning and Community Right-to-Know Act**

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 1.0

Revision Date 09/19/2016

Print Date 04/10/2017

**CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
tert-butyl acetate	540-88-5	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 311/312 Hazards** : Acute Health Hazard  
 Fire Hazard

**SARA 302** : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

acetone	67-64-1	20 %
toluene	108-88-3	10 %

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

toluene	108-88-3	10 %
---------	----------	------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

acetone	67-64-1	20 %
toluene	108-88-3	10 %

**California Prop 65**
**WARNING:** This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

toluene	108-88-3
---------	----------

**The components of this product are reported in the following inventories:**

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL

**SECTION 16. OTHER INFORMATION**
**Further information**

Revision Date : 09/19/2016

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.