

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Trade name : JM LVOC Membrane Adhesive (TPO &amp; EPDM)

## Manufacturer or supplier's details

Company : Johns Manville  
Address : P.O. Box 5108  
Denver, CO USA 80127  
Telephone : +1-303-978-2000  
Emergency telephone : +1-800-424-9300 (CHEMTREC)  
number

Company : Johns Manville Canada Inc.  
Address : 5301 42 Avenue  
Innisfail, AB Canada T4G 1A2  
Telephone : +1-303-978-2000  
Emergency telephone : +1-800-424-9300 (CHEMTREC)  
number

Recommended use of the chemical and restrictions on use

Restrictions on use : For professional users only.

Prepared by : productsafety@jm.com

**SECTION 2. HAZARDS IDENTIFICATION****GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Flammable liquids : Category 2  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Reproductive toxicity : Category 2  
Specific target organ toxicity : Category 3 (Central nervous system)  
- single exposure  
Specific target organ toxicity : Category 2  
- repeated exposure  
Aspiration hazard : Category 1

**GHS label elements**Hazard pictograms : 

Signal word : Danger

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

- Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H361d Suspected of damaging the unborn child.  
H373 May cause damage to organs through prolonged or repeated exposure.
- Precautionary statements : **Prevention:**  
P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P233 Keep container tightly closed.  
P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
- Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: Get medical advice/ attention.  
P331 Do NOT induce vomiting.  
P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
P337 + P313 If eye irritation persists: Get medical advice/ attention.  
P362 Take off contaminated clothing and wash before reuse.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
- Storage:**  
P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.
- Disposal:**  
P501 Dispose of contents/container to an approved facility in

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

accordance with local, regional, national and international regulations.

**Other hazards**

None known.

**SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS****Hazardous components**

Chemical name	CAS-No.	Concentration (%)
tert-butyl acetate	540-88-5	$\geq 30$ - $\leq 60$
acetone	67-64-1	$\geq 10$ - $\leq 30$
toluene	108-88-3	$\geq 5$ - $\leq 10$

**SECTION 4. FIRST AID MEASURES**

- General advice : Move out of dangerous area.  
Consult a physician.  
Show this safety data sheet to the doctor in attendance.  
Symptoms of poisoning may appear several hours later.  
Do not leave the victim unattended.
- If inhaled : Call a physician or poison control centre immediately.  
If unconscious, place in recovery position and seek medical advice.
- In case of skin contact : If skin irritation persists, call a physician.  
Wash off with soap and water.  
If on clothes, remove clothes.
- In case of eye contact : Remove contact lenses.  
Immediately flush eye(s) with plenty of water.  
Protect unharmed eye.  
Keep eye wide open while rinsing.  
If eye irritation persists, consult a specialist.
- If swallowed : Do NOT induce vomiting.  
Keep respiratory tract clear.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.  
Take victim immediately to hospital.
- Most important symptoms and effects, both acute and delayed : irritant effects

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

	Halons Foam
Unsuitable extinguishing media	: High volume water jet
Specific hazards during firefighting	: Do not allow run-off from fire fighting to enter drains or water courses.
Hazardous combustion products	: carbon oxides
Specific extinguishing methods	: Standard procedure for chemical fires. Use a water spray to cool fully closed containers.
Further information	: Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
Special protective equipment for firefighters	: Wear self-contained breathing apparatus for firefighting if necessary.

**SECTION 6. ACCIDENTAL RELEASE MEASURES**

Personal precautions, protective equipment and emergency procedures	: Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Environmental precautions	: Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for containment and cleaning up	: Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SECTION 7. HANDLING AND STORAGE**

Advice on protection against fire and explosion	: Do not spray on a naked flame or any incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
---	---

## JM LVOC Membrane Adhesive (TPO & EPDM)

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

- Advice on safe handling : Avoid formation of aerosol.  
Do not breathe vapours/dust.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Take precautionary measures against static discharges.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Open drum carefully as content may be under pressure.  
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Prevent unauthorized access.  
No smoking.  
Keep container tightly closed in a dry and well-ventilated place.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Observe label precautions.  
Electrical installations / working materials must comply with the technological safety standards.
- Further information on storage stability : Stable at normal ambient temperature and pressure.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
tert-butyl acetate	540-88-5	TWA	200 ppm	ACGIH
		TWA	200 ppm 950 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm 950 mg/m <sup>3</sup>	OSHA
acetone	67-64-1	TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
		TWA	250 ppm 590 mg/m <sup>3</sup>	NIOSH REL
		TWA	1,000 ppm 2,400 mg/m <sup>3</sup>	OSHA
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m <sup>3</sup>	NIOSH REL
		ST	150 ppm 560 mg/m <sup>3</sup>	NIOSH REL
		TWA	200 ppm	OSHA
		CEIL	300 ppm	OSHA
		Peak	500 ppm (10 minutes)	OSHA

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

**Biological occupational exposure limits**

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

**Personal protective equipment**

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection  
Material : Solvent-resistant gloves

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Eye protection : Wear safety glasses with side shields or goggles. Wear face-shield and protective suit for abnormal processing problems.

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

- Skin and body protection : Impervious clothing  
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
- Hygiene measures : Avoid contact with skin, eyes and clothing.  
When using do not eat or drink.  
When using do not smoke.  
Wash hands before breaks and immediately after handling the product.  
Written instructions for handling must be available at the work place.

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : liquid
- Color : yellow
- Odor : strong, sweet
- Odor Threshold : No data available
- pH : No data available
- Melting point/range : No data available
- Boiling point/boiling range : > 37.8 °C
- Flash point : -4 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : Not applicable
- Lower explosion limit : Not applicable
- Vapour pressure : No data available
- Relative vapour density : No data available
- Relative density : No data available
- Density : 0.91 g/cm<sup>3</sup>
- Solubility(ies)  
Water solubility : No data available
- Solubility in other solvents : No data available
- Partition coefficient: n-octanol/water : No data available
- Auto-ignition temperature : not determined

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 1,500 - 3,500 mPa.s
Viscosity, kinematic	: No data available

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: None known.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Strong oxidizing agents Acids and bases
Hazardous decomposition products	: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). nitrogen oxides

**SECTION 11. TOXICOLOGICAL INFORMATION****Acute toxicity****Product:**

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
Acute inhalation toxicity	: Acute toxicity estimate : > 200 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	: Acute toxicity estimate : > 2,000 mg/kg Method: Calculation method

**Acute toxicity****Components:****tert-butyl acetate:**

Acute oral toxicity	: LD50 (Rat, male): 4,100 mg/kg GLP: yes
Acute inhalation toxicity	: LC50 (Rat, male and female): > 2.23 mg/l Exposure time: 4 h Test atmosphere: vapour GLP: yes



**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: No mortality was observed.

Acute dermal toxicity : LD50 (Rabbit, male and female): > 2,000 mg/kg  
GLP: yes

**Acute toxicity****acetone:**

Acute oral toxicity : LD50 (Rat, female): 5,800 mg/kg  
GLP: no

Acute inhalation toxicity : LC50 (Rat, female): 76.0 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
GLP: no

Acute dermal toxicity : LD50 (Guinea pig, male and female): > 7,426 mg/kg  
GLP: no

**Acute toxicity****toluene:**

Acute oral toxicity : LD50 Oral (Rat, male): 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 12,267 mg/kg

**Skin corrosion/irritation****Components:****toluene:**

Species: Rabbit  
Result: Irritating to skin.

**Serious eye damage/eye irritation****Components:****acetone:**

Species: Rabbit  
Result: Eye irritation  
Exposure time: 24 h  
Assessment: Irritating to eyes.  
Method: Draize Test

**IARC**

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

**ACGIH**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Reproductive toxicity****Components:****toluene:**

Reproductive toxicity -  
Assessment

: Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

**STOT - single exposure****Components:****acetone:**

Exposure routes: inhalation (vapour)

Target Organs: Nervous system

Assessment: May cause drowsiness or dizziness.

**STOT - single exposure****toluene:**

Assessment: May cause drowsiness or dizziness.

**STOT - repeated exposure****Components:****toluene:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Components:****toluene:**

May be fatal if swallowed and enters airways.

**Experience with human exposure****Components:****toluene:**

Skin contact:

Remarks:

Prolonged skin contact may defat the skin and produce dermatitis.

**SECTION 12. ECOLOGICAL INFORMATION**

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

**Ecotoxicity**

No data available

**Persistence and degradability****Components:****acetone:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %

**Bioaccumulative potential****Components:****tert-butyl acetate:**

Partition coefficient: n- : log Pow: 1.64 (21.7 °C)  
octanol/water

**acetone:**

Partition coefficient: n- : log Pow: -0.24 (20 °C)  
octanol/water

**toluene:**

Partition coefficient: n- : Pow: 2.7  
octanol/water

**Mobility in soil**

No data available

**Other adverse effects****Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82  
Protection of Stratospheric Ozone - CAA Section 602 Class I  
Substances  
Remarks: This product neither contains, nor was  
manufactured with a Class I or Class II ODS as defined by the  
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +  
B).

Additional ecological : No data available  
information

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Disposal of residual product : Do not dispose of waste into sewer.  
Do not contaminate ponds, waterways or ditches with  
chemical or used container.  
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

Dispose of as unused product.  
Do not re-use empty containers.  
Do not burn, or use a cutting torch on, the empty drum.

**SECTION 14. TRANSPORT INFORMATION****International transport regulations**

Land transport

USDOT (Special Provision 383): UN1133, Adhesives, 3, III

TDG: UN1133, Adhesives, 3, II

LIMITED QUANTITY if shipped in inner packagings not over 5.0 L (1.3 gallons) net capacity each,  
packed in a strong outer packaging.

Sea transport

IMDG: UN1133, Adhesives, 3, II

Air transport

IATA/ICAO: UN1133, Adhesives, 3, II

**SECTION 15. REGULATORY INFORMATION****TSCA list**

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : No substances are subject to TSCA 12(b) export notification requirements.

**EPCRA - Emergency Planning and Community Right-to-Know Act****CERCLA Reportable Quantity**

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
tert-butyl acetate	540-88-5	5000	*

\*: Calculated RQ exceeds reasonably attainable upper limit.

**SARA 304 Extremely Hazardous Substances Reportable Quantity**

This material does not contain any components with a section 304 EHS RQ.

**SARA 311/312 Hazards** : Flammable (gases, aerosols, liquids, or solids)  
Serious eye damage or eye irritation  
Reproductive toxicity  
Specific target organ toxicity (single or repeated exposure)  
Skin corrosion or irritation  
Aspiration hazard

**JM LVOC Membrane Adhesive (TPO & EPDM)**

Version 2.1

Revision Date 07/02/2019

Print Date 07/02/2019

**SARA 302** : This material does not contain any components with a section 302 EHS TPQ.

**SARA 313** : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene	108-88-3	5 - 10 %
---------	----------	----------

**Clean Air Act**

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):


toluene	108-88-3	5 - 10 %
---------	----------	----------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

acetone	67-64-1	10 - 30 %
toluene	108-88-3	5 - 10 %

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)**

 **WARNING:** This product can expose you to chemicals including toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**The components of this product are reported in the following inventories:**

TSCA : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

---

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date : 07/02/2019

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.