

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM TPO LVOC Edge Sealant – Clear

Manufacturer or supplier's details

Company : Johns Manville
Address : P.O. Box 5108
Denver, CO USA 80127
Telephone : +1-303-978-2000
Emergency telephone : +1-800-424-9300 (CHEMTREC)
number

Company : Johns Manville Canada Inc.
Address : 5301 42 Avenue
Innisfail, AB Canada T4G 1A2
Telephone : +1-303-978-2000
Emergency telephone : +1-800-424-9300 (CHEMTREC)
number

Recommended use of the chemical and restrictions on use

Recommended use : Sealant

Restrictions on use : For professional and industrial installation and use only.

Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION**GHS classification in accordance with 29 CFR 1910.1200 (OSHA HCS 2012) and the Hazardous Products Regulations (WHMIS 2015)**

Flammable liquids : Category 2

Skin sensitisation : Category 1

Reproductive toxicity : Category 2

Specific target organ toxicity : Category 2
- repeated exposure**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H361d Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

Precautionary statements

:

Prevention:

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P308 + P313 IF exposed or concerned: Get medical advice/ attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P363 Wash contaminated clothing before reuse.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS
Chemical nature

Adhesives and/or sealants

Hazardous components

Chemical name	CAS-No.	Concentration (%)
benzene, 1-chloro-4-(trifluoromethyl)-	98-56-6	>= 60 - <= 80
toluene	108-88-3	>= 5 - <= 10

Actual concentration or concentration range is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

General advice	:	Move out of dangerous area. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended. Symptoms of poisoning may appear several hours later.
If inhaled	:	Remove to fresh air immediately. Get medical attention immediately. If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact	:	In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Call a physician if irritation develops or persists.
In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 5 minutes. If easy to do, remove contact lens, if worn. Protect unharmed eye. If eye irritation persists, consult a specialist.
If swallowed	:	DO NOT induce vomiting unless directed to do so by a physician or poison control center. Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician or Poison Control Centre immediately.
Most important symptoms and effects, both acute and delayed	:	May cause an allergic skin reaction. Suspected of damaging the unborn child. May cause damage to organs through prolonged or repeated exposure.
Protection of first-aiders	:	If potential for exposure exists refer to Section 8 for specific personal protective equipment.
Notes to physician	:	Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Carbon dioxide (CO ₂) Water spray Dry chemical Foam Halons
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Vapours may form flammable mixture with air Vapours are heavier than air and may spread along floors.
Hazardous combustion products	:	carbon oxides Hydrogen chloride gas Hydrogen fluoride

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Ensure adequate ventilation.
Use personal protective equipment.
Evacuate personnel to safe areas.
Keep people away from and upwind of spill/leak.
Remove all sources of ignition.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Should not be released into the environment.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

- Advice on protection against fire and explosion : Use explosion-proof equipment.
Electrical equipment should be protected to the appropriate standard.
Take measures to prevent the build up of electrostatic charge.
Use only in area provided with appropriate exhaust ventilation.
Keep away from open flames, hot surfaces and sources of ignition.
- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.
Keep away from flames, such as a pilot light, and any object that sparks, such as an electric motor.
Do not use sparking tools.
Use only in area provided with appropriate exhaust ventilation.
Provide exhaust ventilation close to floor level.
Do not breathe vapours or spray mist.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
For personal protection see section 8.
- Conditions for safe storage : Keep containers tightly closed in a dry, cool and well-ventilated place.
To maintain product quality, do not store in heat or direct sunlight.
Use explosion-proof equipment.
- Materials to avoid : Keep away from oxidizing agents and strongly acid or alkaline materials.

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

Recommended storage temperature : 16 - 27 °C
 Storage period : 12 Months
 Further information on storage stability : Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
toluene	108-88-3	TWA	20 ppm	ACGIH
		TWA	100 ppm 375 mg/m ³	NIOSH REL
		ST	150 ppm 560 mg/m ³	NIOSH REL
		TWA	200 ppm	OSHA
		CEIL	300 ppm	OSHA
		Peak	500 ppm (10 minutes)	OSHA

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
toluene	108-88-3	Toluene	In blood	Prior to last shift of workweek	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
		o-Cresol	Urine	End of shift (As soon as possible after exposure ceases)	0.3 mg/g Creatinine	ACGIH BEI

Engineering measures : Provide exhaust ventilation close to floor level.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection Material	:	Solvent-resistant gloves
Remarks	:	Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.
Eye protection	:	Wear safety glasses with side shields or goggles.
Skin and body protection	:	Wear protective clothing, such as long-sleeved shirts and pants.
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety practice. Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	colorless
Odour	:	pleasant, acetone-like
Odour Threshold	:	No data available
pH	:	No data available
Melting point/range	:	not determined
Initial boiling point and boiling range	:	139 °C
Flash point	:	4 °C
Evaporation rate	:	2 (n-Butyl acetate = 1.0)
Flammability (solid, gas)	:	Not applicable

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

Upper explosion limit	: 10.5 %(V)
Lower explosion limit	: 0.9 %(V)
Vapour pressure	: 40 hPa (20 °C)
Relative vapour density	: No data available
Relative density	: No data available
Density	: 1.20 g/cm ³ (20 °C)
Water solubility	: No data available
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: 480 °C
Thermal decomposition	: No data available
Viscosity, dynamic	: No data available
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Vapours may form explosive mixture with air. Stable under recommended storage conditions.
Conditions to avoid	: Heat, flames and sparks.
Incompatible materials	: Oxidizing agents Strong acids and strong bases Amines Ammonia Copper halogenated compounds isocyanates
Hazardous decomposition products	: In case of fire hazardous decomposition products may be produced such as: carbon oxides Hydrogen chloride gas Hydrogen fluoride

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

Not classified based on available information.

Product:

Acute inhalation toxicity : Acute toxicity estimate : > 200 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate : > 2,000 mg/kg
Method: Calculation method

Acute toxicity**Components:****benzene, 1-chloro-4-(trifluoromethyl)-:**

Acute oral toxicity : LD50 (Rat, male): 5,546 mg/kg
GLP: no

Acute inhalation toxicity : LC50 (Rat, male and female): > 32.03 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
GLP: yes

Acute dermal toxicity : LD50 (Rabbit): > 3,300 mg/kg
GLP: no

Acute toxicity**toluene:**

Acute oral toxicity : LD50 Oral (Rat, male): 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat): 28.1 mg/l
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 12,267 mg/kg

Skin corrosion/irritation**Components:****toluene:**

Species: Rabbit
Result: Irritating to skin.

Respiratory sensitisation: Not classified based on available information.

Respiratory or skin sensitisation**Components:****benzene, 1-chloro-4-(trifluoromethyl)-:**

Test Type: local lymph node assay (LLNA)
Exposure routes: Skin contact

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

Species: Mouse
Method: OECD Test Guideline 429
Result: The product is a skin sensitiser, sub-category 1B.

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
OSHA	No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity**Components:****toluene:**

Reproductive toxicity - Assessment : Suspected of damaging the unborn child., Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure**Components:****toluene:**

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure**Components:****toluene:**

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Components:**toluene:**

May be fatal if swallowed and enters airways.

Experience with human exposure**Components:****toluene:**

Skin contact:

Remarks: Prolonged skin contact may defat the skin and produce dermatitis.

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

Further information**Product:**

Remarks: Solvents may degrease the skin.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****benzene, 1-chloro-4-(trifluoromethyl)-:**

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 3 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 2 mg/l
aquatic invertebrates : Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae : NOEC (Pseudokirchneriella subcapitata (green algae)): 0.41
mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability**Components:****benzene, 1-chloro-4-(trifluoromethyl)-:**

Biodegradability : Result: According to the results of tests of biodegradability this
product is not readily biodegradable.
Method: OECD Test Guideline 301D

Bioaccumulative potential**Components:****benzene, 1-chloro-4-(trifluoromethyl)-:**

Bioaccumulation : Bioconcentration factor (BCF): 121.8

Partition coefficient: n- : Pow: 5,030 (25 °C)
octanol/water : log Pow: 3.7 (25 °C)

toluene:

Partition coefficient: n- : Pow: 2.7
octanol/water

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

Mobility in soil

No data available

Other adverse effects**Product:**

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I
Substances

Remarks: This product neither contains, nor was
manufactured with a Class I or Class II ODS as defined by the
U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +
B).

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of contents/container to an approved facility in
accordance with local, regional, national and international
regulations.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION**International transport regulations**

Land transport

USDOT (Special Provision 149): UN1133, Adhesives, 3, II

TDG: UN1133, Adhesives, 3, II

LIMITED QUANTITY if shipped in inner packagings not over 5.0 L (1.3 gallons) net capacity each,
packed in a strong outer packaging.

Sea transport

IMDG: UN1133, Adhesives, 3, II

Air transport

IATA/ICAO: UN1133, Adhesives, 3, II

SECTION 15. REGULATORY INFORMATION**TSCA list**

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : The following substance(s) is/are
subject to TSCA 12(b) export
notification requirements:
benzene, 1-chloro-4-(trifluoromethyl)-

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
toluene	108-88-3	1000	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Flammable (gases, aerosols, liquids, or solids)
 Respiratory or skin sensitisation
 Reproductive toxicity
 Specific target organ toxicity (single or repeated exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : The following components are subject to reporting levels established by SARA Title III, Section 313:

toluene	108-88-3	5 - 10 %
---------	----------	----------

Clean Air Act

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 12 (40 CFR 61):

toluene	108-88-3	5 - 10 %
---------	----------	----------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

toluene	108-88-3	5 - 10 %
---------	----------	----------

California Prop. 65

⚠️ WARNING: This product can expose you to chemicals including benzene, 1-chloro-4-(trifluoromethyl)-, which is/are known to the State of California to cause cancer, and toluene, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

TSCA : On the inventory, or in compliance with the inventory

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

JM TPO LVOC Edge Sealant – Clear

Version 2.0

Revision Date 03/23/2020

Print Date 03/23/2020

Further information

Revision Date : 03/23/2020

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.