

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Trade name : JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Manufacturer or supplier's details

Company : Johns Manville
 Address : P.O. Box 5108
 Denver, CO USA 80217-5108
 Telephone : +1-303-978-2000
 Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

Company : Johns Manville Canada Inc.
 Address : 5301 42 Avenue
 Innisfail, AB Canada T4G 1A2
 Telephone : +1-303-978-2000
 Emergency telephone number : 24-Hour Number: +1-800-424-9300 (CHEMTREC)

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives
 Restrictions on use : For professional users only.
 Prepared by : productsafety@jm.com

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200 and the Hazardous Products Regulations

Gases under pressure : Compressed gas

Acute toxicity (Oral) : Category 4

GHS label elements

Hazard pictograms :



Signal word : Warning

Hazard statements : H280 Contains gas under pressure; may explode if heated.
 H302 Harmful if swallowed.

Precautionary statements : **Prevention:**
 P264 Wash skin thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
Response:
 P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

Storage:

P410 + P403 Protect from sunlight. Store in a well-ventilated place.

Disposal:

P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS
Chemical nature

Mixture

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
polypropylene glycol	25322-69-4	>= 30 - < 60
diethylene glycol	111-46-6	>= 5 - < 10

Actual concentration or concentration range is withheld as a trade secret

Relevant ingredients

Chemical name	CAS-No.	Concentration (% w/w)
1-propene, 1,3,3,3-tetrafluoro-, (1E)-	29118-24-9	>= 10 - < 30 %

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
- In case of skin contact : In case of contact, flush skin with plenty of water for at least 5 minutes.
Call a physician if irritation develops or persists.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 5 minutes.
If easy to do, remove contact lens, if worn.
Protect unharmed eye.
If eye irritation persists, consult a specialist.
- If swallowed : DO NOT induce vomiting unless directed to do so by a physician or poison control center.
Gently wipe or rinse the inside of the mouth with water.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician or Poison Control Centre immediately.
- Most important symptoms and effects, both acute and delayed : None known.
- Protection of first-aiders : If potential for exposure exists refer to Section 8 for specific personal protective equipment.

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Water spray Carbon dioxide (CO ₂) Dry chemical Foam
Unsuitable extinguishing media	:	High volume water jet
Specific hazards during firefighting	:	Contains gas under pressure; may explode if heated. Cool closed containers exposed to fire with water spray.
Hazardous combustion products	:	carbon oxides Hydrogen fluoride
Specific extinguishing methods	:	Use a water spray to cool fully closed containers. Remove undamaged containers from fire area if it is safe to do so.
Further information	:	Standard procedure for chemical fires.
Special protective equipment for firefighters	:	Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Immediately evacuate personnel to safe areas. Use personal protective equipment.
Environmental precautions	:	Prevent further leakage or spillage if safe to do so. The product should not be allowed to enter drains, water courses or the soil.
Methods and materials for containment and cleaning up	:	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Fire or intense heat may cause violent rupture of packages.
Advice on safe handling	:	Avoid exposure - obtain special instructions before use. Do not eat, drink or smoke when using this product. Use only with adequate ventilation. Avoid contact with skin and eyes. Wash skin thoroughly after handling. For personal protection see section 8.
Conditions for safe storage	:	Protect from sunlight. Store in a well-ventilated place.
Materials to avoid	:	Explosives Oxidizing agents
Recommended storage	:	60 - 90 °F / 16 - 32 °C

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1 Revision Date 05/19/2023 Print Date 05/19/2023

temperature
Further information on storage stability : Keep in a dry, cool and well-ventilated place.
Do not freeze.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
polypropylene glycol	25322-69-4	TWA (aerosol)	10 mg/m3	US WEEL
diethylene glycol	111-46-6	TWA	10 mg/m3	US WEEL

Engineering measures : Use a local and/or general ventilation system.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

- Material : butyl rubber
- Material : Nitrile rubber
- Material : Polyvinyl alcohol ("PVA").

Remarks : Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Eye protection : Wear safety glasses with side shields or goggles.
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Wear protective clothing, such as long-sleeved shirts and pants.
Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits) to avoid exposed skin surfaces.
Remove and wash contaminated clothing before re-use.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice.
When using do not eat or drink.

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

When using do not smoke.
Wash hands before breaks and at the end of workday.
Written instructions for handling must be available at the work place.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Compressed gas
Colour	: red
Odour	: mild, sweet
Odour Threshold	: No data available
pH	: No data available
Melting point/freezing point	: No data available
Initial boiling point and boiling range	: Not applicable
Flash point	: Not applicable
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: > 13,790 hPa
Relative vapour density	: No data available
Relative density	: ca. 1.03(Water = 1.0)
Density	: ca. 1.03 g/cm ³
Solubility(ies)	
Water solubility	: partly soluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Thermal decomposition	: No data available
Viscosity	
Viscosity, dynamic	: 280 mPa.s
Viscosity, kinematic	: No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: No dangerous reaction known under conditions of normal use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: Contact with isocyanates will cause polymerization. Stable under normal conditions.
Conditions to avoid	: Do not expose to temperatures above: 177 °C
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: carbon oxides Fluorocarbons

SECTION 11. TOXICOLOGICAL INFORMATION**Acute toxicity**

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

Product:

 Acute oral toxicity : Acute toxicity estimate : 1,124 mg/kg
 Method: Calculation method

 Acute dermal toxicity : Acute toxicity estimate : > 5,000 mg/kg
 Method: Calculation method

Components:
polypropylene glycol:

 Acute oral toxicity : LD50 (Rat, male and female): > 5,000 mg/kg
 Method: OECD Test Guideline 401
 GLP: yes

 Acute inhalation toxicity : LC50 (Rat, male and female): > 2.34 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Method: EPA OPP 81-3
 GLP: yes
 Assessment: The substance or mixture has no acute inhalation toxicity

 Acute dermal toxicity : LD50 (Rabbit, male and female): > 3,000 mg/kg
 Method: OECD Test Guideline 402
 GLP: yes

diethylene glycol:

Acute oral toxicity : LD50 (Humans): > 300 - 2,000 mg/kg

 Acute inhalation toxicity : LC50 (Rat): > 4.6 mg/l
 Exposure time: 4 h
 Test atmosphere: dust/mist
 Assessment: The substance or mixture has no acute inhalation toxicity
 Remarks: No mortality was observed.

Acute dermal toxicity : LD50 (Rabbit): 13,300 mg/kg

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA (29 CFR 1910 Subpart Z, Toxic and Hazardous Substances).

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

Ecotoxicity**Components:****polypropylene glycol:**

- Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes
Remarks: No toxicity at the limit of solubility
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 105.8 mg/l
End point: Immobilization
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes
- Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

diethylene glycol:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 75,200 mg/l
End point: mortality
Exposure time: 96 h
Test Type: flow-through test
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l
Exposure time: 24 h
Test Type: static test
Method: DIN 38412
- Toxicity to algae/aquatic plants : EC10 (algae): 100 mg/l
Remarks: The value is given based on a SAR/AAR approach using OECD Toolbox, DEREK, VEGA QSAR models (CAESAR models), etc.

Persistence and degradability**Components:****diethylene glycol:**

- Biodegradability : aerobic
Result: Readily biodegradable.
Biodegradation: 90 - 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

Bioaccumulative potential**Components:****polypropylene glycol:**

Partition coefficient: n-octanol/water : log Pow: 0.01 (77 °F / 25 °C)

diethylene glycol:Bioaccumulation : Species: Leuciscus idus (Golden orfe)
Bioconcentration factor (BCF): 100
Exposure time: 3 d
Concentration: 0.05 mg/l

Partition coefficient: n-octanol/water : log Pow: -1.98 (68 °F / 20 °C)

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

Waste from residues : Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION**International transport regulations**

Land transport

USDOT: UN3500, Chemical under pressure, n.o.s. (1,3,3,3-Tetrafluoropropene, Nitrogen), 2.2
TDG: UN3500, Chemical under pressure, n.o.s. (1,3,3,3-Tetrafluoropropene, Nitrogen), 2.2

Sea transport

IMDG: UN3500, Chemical under pressure, n.o.s. (1,3,3,3-Tetrafluoropropene, Nitrogen), 2.2

Air transport

IATA/ICAO: UN3500, Chemical under pressure, n.o.s. (1,3,3,3-Tetrafluoropropene, Nitrogen), 2.2

SECTION 15. REGULATORY INFORMATION**TSCA list**

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

TSCA - 5(a) Significant New Use Rule List of Chemicals : No substances are subject to a Significant New Use Rule.

U.S. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpart D) : No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Gases under pressure
Acute toxicity (any route of exposure)

SARA 302 : This material does not contain any components with a section 302 EHS TPQ.

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

The following chemical(s) are listed as HAP under the U.S. Clean Air Act, Section 112 (40 CFR 61):

diethylene glycol	111-46-6	5 - 10 %
-------------------	----------	----------

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

The following chemical(s) are listed under the U.S. Clean Air Act Section 111 SOCM I Intermediate or Final VOC's (40 CFR 60.489):

polypropylene glycol	25322-69-4	30 - 60 %
diethylene glycol	111-46-6	5 - 10 %

California Prop. 65

This product does not require a warning under the California Safe Drinking Water and Toxic Enforcement Act (Proposition 65).

The components of this product are reported in the following inventories:

TSCA : All substances listed as active on the TSCA inventory

DSL : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

Revision Date : 05/19/2023

Full text of other abbreviations

US WEEL : USA. Workplace Environmental Exposure Levels (WEEL)

US WEEL / TWA : 8-hr TWA

JM Two-Part Urethane Insulation Adhesive (UIA) Canister – Part 2

Version 2.1

Revision Date 05/19/2023

Print Date 05/19/2023

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.