

HOMEOWNER _____ DATE _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

RECORD OF INSTALLATION

BLOWING WOOL				BATTS AND ROLLS		
<input type="checkbox"/> New Construction	If Retrofit:					
<input type="checkbox"/> Retrofit	Depth of Previous Insulation			in.		
Number of bags used		Estimated R-value of Previous Installation				
Area Insulated	sq. ft.	Types of Previous Insulation in Attic				
Thickness of Insulation	in.					
R-value of Insulation						

ATTIC PROTECTOR BLOW-IN COVERAGE CHART

R-VALUE (hr•sq.ft.°F/BTU)	MINIMUM INSTALLED THICKNESS (in.)	SETTLED THICKNESS (in.)	BAGS PER 1,000 SQ. FT.	MAXIMUM NET COVERAGE* (sq.ft./bag)	MINIMUM WEIGHT (lbs./sq.ft.)
To obtain an insulation resistance (R) of	Installed insulation should not be less than:	Expected thickness after long-term settling has occurred	Minimum number of bags per 1,000 sq.ft. of net area:	Contents of this bag should not cover more than:	The weight per sq. ft. of installed insulation should not be less than:
11	5.0	4.9	5.1	192.2	0.131
13	5.8	5.7	6.0	162.3	0.155
19	8.2	8.1	9.0	109.3	0.231
22	9.4	9.2	10.5	93.4	0.270
26	10.9	10.8	12.7	77.9	0.324
30	12.4	12.3	14.9	66.5	0.379
38	15.3	15.2	19.4	51.0	0.494
44	17.4	17.3	22.9	43.3	0.583
49	19.1	18.9	25.9	38.3	0.658
60	22.6	22.5	32.6	30.5	0.827

INSULATION CONTRACTOR SIGNATURE _____ DATE _____

COMPANY _____ ADDRESS _____ PHONE _____

HOME BUILDER SIGNATURE _____ DATE _____

COMPANY _____ ADDRESS _____ PHONE _____