

R-VALUE (hr•sq.ft.°F/BTU)	MINIMUM INSTALLED THICKNESS (in.)	SETTLED THICKNESS (in.)	BAGS PER 1,000 SQ. FT.	MAXIMUM NET COVERAGE (sq.ft./bag)	MINIMUM WEIGHT (lbs./sq.ft.)
To obtain an insulation resistance (R) of:	Installed insulation should not be less than:	Expected thickness after long-term settling has occurred:	Minimum number of bags per 1,000 sq.ft. of net area:	Contents of this bag should not cover more than:	The weight per sq. ft. of installed insulation should not be less than:
11	4.25	4.25	4.6	215.9	0.15
13	5.00	5.00	5.5	181.3	0.17
19	7.00	7.00	8.0	125.4	0.25
22	8.00	8.00	9.3	108.0	0.29
26	9.50	9.50	11.2	88.9	0.35
30	10.75	10.75	13.0	77.1	0.41
38	13.50	13.50	17.0	59.0	0.53
40	14.00	14.00	17.7	56.5	0.56
44	15.25	15.25	19.6	50.9	0.62
49	17.00	17.00	22.4	44.6	0.71
50	17.25	17.25	22.8	43.9	0.72
60	20.25	20.25	27.9	35.8	0.88
64	21.50	21.50	30.0	33.3	0.95
68	22.75	22.75	32.3	31.0	1.02
70	23.25	23.25	33.2	30.1	1.05
72	24.00	24.00	34.6	28.9	1.09
76	25.00	25.00	36.5	27.4	1.15
80	26.25	26.25	38.9	25.7	1.22
84	27.50	27.50	41.3	24.2	1.30
88	28.50	28.50	43.4	23.1	1.37
92	29.75	29.75	45.9	21.8	1.45
96	30.75	30.75	48.0	20.8	1.51
100	32.00	32.00	50.7	19.7	1.60