

JM Climate Pro® Fiber Glass Blowing Wool

Your home has been professionally insulated to provide superior thermal resistance.

Homeowner's Name _____ Date _____

Address _____

City _____ State _____ Zip _____

RECORD OF INSTALLATION

BLOWING WOOL

New Construction If Retrofit:

Retrofit Depth of Previous Insulation _____ in.

Number of bags used _____ Estimated R-value of Previous Installation _____

Area Insulated _____ sq. ft. Types of Previous Insulation in Attic _____

Thickness of Insulation _____ in.

R-value of Insulation _____

BATTS AND ROLLS

	R-VALUE	THICKNESS	AREA INSULATED
Ceilings	_____	_____ in.	_____ sq. ft.
	_____	_____ in.	_____ sq. ft.
Walls	_____	_____ in.	_____ sq. ft.
	_____	_____ in.	_____ sq. ft.
Floors	_____	_____ in.	_____ sq. ft.
	_____	_____ in.	_____ sq. ft.

CLIMATE PRO INSULATION, BAG WEIGHT - 28.5 LB. MINIMUM

R-VALUE (hr•sq.ft.°F/BTU)	MINIMUM INSTALLED THICKNESS (in.)	SETTLED THICKNESS (in.)	BAGS PER 1,000 SQ. FT.	MAXIMUM NET COVERAGE (sq.ft./bag)	MINIMUM WEIGHT (lbs./sq.ft.)
To obtain an insulation resistance (R) of	Installed insulation should not be less than:	Expected thickness after long-term settling has occurred	Minimum number of bags per 1,000 sq.ft. of net area:	Contents of this bag should not cover more than:	The weight per sq. ft. of installed insulation should not be less than:
11	4.3	4.3	4.8	209	0.150
13	5.0	5.0	5.7	176	0.179
19	7.2	7.2	8.4	118	0.266
22	8.3	8.3	9.9	101	0.310
26	9.7	9.7	11.8	85	0.371
30	11.1	11.1	13.7	73	0.432
38	13.8	13.8	17.7	56	0.559
44	15.7	15.7	20.8	48	0.656
49	17.3	17.3	23.5	43	0.739
60	20.7	20.7	29.5	34	0.928

See reverse to determine adjustment in coverage for Climate Pro Insulation installed in Minnesota.

Insulation Contractor Signature _____ Date _____

Company _____ Address _____ Phone _____

Home Builder Signature _____ Date _____

Company _____ Address _____ Phone _____

