

JM IV HFO
Corbond® Closed Cell SPF
FREQUENTLY ASKED QUESTIONS

1. What is JM IV HFO?

JM IV HFO is a closed cell spray foam formula and is the latest release in JM's Spray Foam product lineup. It is a two-component Spray Polyurethane Foam (SPF) insulation system featuring closed cell technology.

2. How does JM IV HFO Closed Cell differ from other Corbond® IV formulas?

JM IV HFO is a budget-friendly SPF formula, offering the same superior performance as other JM closed cell formulas at a competitive price.

3. What is the shelf life of JM IV HFO B-side?

Six months.

4. What other benefits does JM IV HFO have?

- Allows for one-hour re-entry times for trades when the space is ventilated at 10 air changes per hour (ACH).
- Features a one-hour fire-resistance-rated wall assembly.

5. What color will JM IV HFO be once installed?

JM IV HFO will feature the same signature Corbond® lavender color as other Corbond closed cell SPF insulation.

6. What color 55-gallon drums will JM IV HFO come in?

Purple.

7. Will installers need to make any updates to their equipment?

No. This formula performs similarly to other Corbond closed cell formulas.

8. Do I get the same thermal and acoustic performance as previous generations of Corbond closed cell spray foam products?

Yes. JM IV HFO has equivalent finished product performance.

9. How is JM IV HFO shipped?

JM IV HFO can be shipped in full truckloads of A and B quantities or top-loaded with JM's other insulation products from our fiberglass plants.

10. Will the manufacturing installers need to make any processing changes?

Please see the technical data sheet for all processing settings; however, in general, the operating temperature of the A and B sides and hose temperatures are recommended to be similar to other JM closed cell formulas.

11. Have both Side A and Side B been updated?

No. Only the B Side formula. The Side A has not changed. JM's Side A works with all JM closed and open cell SPF Side B formulas.

12. Where can I get JM IV HFO?

Please contact your JM sales representative about pricing and availability.

Visit our website at www.JM.com or call 800-654-3103 | Building Insulation Division P.O. Box 5108 | Denver, CO 80217-5108