

HOMEOWNER _____ DATE _____

ADDRESS _____

CITY _____ STATE _____ ZIP _____

JM SPIDER FIBERGLASS BLOWING WOOL

	R-VALUE	THICKNESS	COVERAGE AREA	NUMBER OF BAGS USED
Ceilings		in.	sq. ft.	
		in.	sq. ft.	
Walls		in.	sq. ft.	
		in.	sq. ft.	
Floors		in.	sq. ft.	
		in.	sq. ft.	

The higher the R-value, the greater the insulating power.

WALL AND OVERHEAD COVERAGE FOR JM SPIDER PLUS BLOW-IN CUSTOM FIBERGLASS INSULATION

Note: Minimum installed density for overhead 2.2 lbs/ft³ Minimum installed wall density is 1.5 lbs/ft³

WOOD FRAME					
Thermal Resistance	Cavity Depth	Minimum Installed Density	Minimum Mass Per Unit Area	Maximum Net Coverage*	Minimum Bag Usage Per:
R-value	inches	lbs/ft ³	lbs/ft ²	ft ² /bag	1000 ft ²
14	3.5	1.5	0.44	68.6	14.6
15		1.8	0.53	57.1	17.5
22	5.5	1.5	0.69	43.6	22.9
23		1.8	0.83	36.4	27.5
29	7.25	1.5	0.91	33.1	30.2
30		1.8	1.09	27.6	36.3
37	9.25	1.5	1.16	25.9	38.5
38		1.8	1.39	21.6	46.3
45	11.25	1.5	1.41	21.3	46.9
47		1.8	1.69	17.8	56.3
STEEL STUDS, PURLINS, ENGINEERED LUMBER, ETC.					
16	4.0	1.5	0.50	60.0	16.7
17		1.8	0.60	50.0	20.0
24	6.0	1.5	0.75	40.0	25.0
25		1.8	0.90	33.3	30.0
32	8.0	1.5	1.00	30.0	33.3
33		1.8	1.20	25.0	40.0
40	10.0	1.5	1.25	24.0	41.7
41		1.8	1.50	20.0	50.0
48	12.0	1.5	1.50	20.0	50.0
50		1.8	1.80	16.7	60.0

*Net coverage area per bag, does not include framing adjustment.

INSULATION CONTRACTOR SIGNATURE _____ DATE _____

COMPANY _____ ADDRESS _____ PHONE _____

HOME BUILDER SIGNATURE _____ DATE _____

COMPANY _____ ADDRESS _____ PHONE _____