

Bulletin Number: T26-001

Date: March 17, 2026

Distribution: External

Johns Manville Peak Advantage® Guarantee Requirements for JM SECUROCK® Gypsum-Fiber Roof Board in Modified Asphalt and EPDM Systems

In a continued effort to ensure JM and our approved contractors provide the best possible roof systems to our end customers, JM has established the following requirements for projects using modified asphalt or EPDM systems that will be requesting a JM Peak Advantage® NDL Guarantee:

JM SECUROCK® Gypsum-Fiber board thickness must be ½” or greater when installing:

- Any modified APP systems
- Any modified SBS systems
- Any adhered EPDM system

Specifically for modified APP and SBS Systems:

Regardless of attachment method, all plies must be reinforced with polyester or composite reinforcement only, including:

- Base plies
- Inter plies
- Cap plies

Fiber glass reinforcement is not permitted for any ply within these systems.

*Additionally, fiber glass reinforced Built-Up Roofing (BUR) membranes are no longer permitted for use with JM SECUROCK Gypsum-Fiber.

Please visit www.jm.com/roofing to view the latest system requirements and installation guidelines or contact JM Guarantee Services at (800) 922-5922 option 3.

Rick Gustin
Owner Services Technical Manager | Roofing Systems