

## Features and Components

**Use:** JM One-Part Pourable Sealer is used as a penetration pocket filler.

**Type:** One-part polyether sealant.

**Color:** Grey



Component

**SE**  
Sealant

Type

**FP**  
Penetration

Single Ply

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
<b>Do Not Use in Multi-Ply systems</b>								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<b>Used to seal non-standard penetrations in all Single Ply systems</b>							

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

## Energy and the Environment

Maximum VOC	<16 g/l (EPA Method 24)
This product may be used in jurisdictions limiting VOC (volatile organic compounds) content of single ply roofing adhesive to no greater than 250 g/l.	

## Physical Properties

Property	JM One-Part Pourable Sealer
Specific Gravity @ 77°F (25°C)	1.39
Service Temperature	-40 F to 200 F

## Precautions

*Johns Manville One-Part Pourable Sealer should be shipped and stored in a cool dry area. Keep all bags tightly sealed while in storage. It may cause eye and skin irritation, and may cause an allergic skin reaction and/or serious eye damage. Avoid contact with skin and eyes. Use impervious clothing, rubber gloves and eye protection to avoid prolonged or repeated contact with skin and eyes. Read the SDS, and container label and follow all safety instructions.*

## Installation/Application



Pour

- Apply when ambient temperature is above 40°F (5°C) and rain is not anticipated for at least 4 hours. Do Not Thin.
- Refer to the online application instructions guide and the product label for proper utilization of this sealant.

## Packaging and Coverage

Container Size	Box of four - 0.5 gal (1.9 l) pouches
Shipping Weight (approx.)	26 lb (11.79 kg)/box
Coverage Rate*	122 in <sup>2</sup> /pouch (0.08 m <sup>2</sup> /pouch) at 2" (5.08 cm) thick

\* Coverage, open and dry time rates can vary dramatically depending on the particular substrate and environmental conditions. Coverage rates stated herein are approximate only.

## Storage

Shelf Life	12 months from manufacture date at 70°F and 50% relative humidity.
Storage Conditions	Clean, dry, indoor environment, out of direct sunlight, in an unopened container
Temperature Range	Handles best at room temperature. Product will not freeze. Elevated temperatures or humidity may reduce shelf life significantly.

## Exposure Window

Squeeze excess air from pouch and replace cap to save unused sealant. Opened product should be used within 30 days.