

JM Coating Polyester Reinforcing Fabric

Features and Components

Use:

JM Coating Polyester Reinforcing Fabric is a stitch-bonded polyester used in JM Coatings liquid-applied systems. The soft, flexible fabric is designed for use around penetrations, or roof mounted equipment, curbs and seams, to improve tear strength, puncture resistance, and crack bridging capabilities. It is a non-woven, fabric reinforcement.

Color: White

Features: Improve tear strength, puncture resistance, and crack

bridging capabilities.



Liquid
CO
Coating



Liquid Applied Multi-Ply Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Ply	BUR		APP*		SBS				
Aulti-I	НА	CA	CA	HW	HA	CA	HW	SA	MF
Ž	Compatible with the selected Multi-Ply systems above *APP cap sheet only						only		

줃	TP0			PVC			EPDM			
ae	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Si	Compatible with the selected Single Ply systems above									

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Physical Properties

Pr	operties	JM Coating Fleece			
	Tensile Strength (ASTM D5034)	74 lbs (warp)	45 lbs (fill)		
Strength	Elongation, (ASTM D5034) %	21.3% (warp)	51.3% (fill)		
Stre	Ball Burst (ASTM D3787)	20>daN			
	Trapezoid (ASTM D117)	24>	daN		
on gevity	Thickness (ASTM D1777)	0.18 in			
Long	Weight	3 oz/yd²			

Installation/Application

• Please refer to JM Coatings Application Guide.

Packaging and Coverage

Fleece Widths	12" (30.5 cm)	6" (15.2 cm)	4" (10.2 cm)	
Fleece Length	300' (91.4 m)	300' (91.4 m)	300' (91.4 m)	
Fleece Coverage (net)	300 ft ² (27.9 m ²)	150 ft ² (13.9 m ²)	100 ft ² (9.3 m ²)	

^{*}Net coverage accounts for 4" laps required for field fleece.

Storage

Shelf Life	Indefinite with proper storage
Storage Conditions	Clean, dry, indoor environment