

Features and Components

Use: To easily form flashings around corners and penetrations. Specifically designed for use in areas that cannot be properly detailed with cured EPDM membrane.

Materials: 60 mil (1.52 mm) thick, uncured EPDM with a release liner and a factory laminated, self-adhering EPDM tape.

Color: Black



Component

A
Accessory

Single Ply

Type

FW
Flashing Wall

FC
Curb/Corner

FP
Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
Do not use in Multi-Ply systems									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

- Prime EPDM membrane with JM Tape Primer or JM Tape Primer (Low VOC) before applying to JM EPDM Peel & Stick Flashing.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Sizes	6" x 100' (15.24 cm x 30.48 m)	9" x 50' (22.86 cm x 15.24 m)	12" x 50' (30.48 cm x 15.24 m)
Thickness: Membrane Tape Total	0.060" (1.52 mm) 0.030" (0.76 mm) 0.090" (2.28 mm)		
Coverage	50 ft ² (4.65 m ²)	37.5 ft ² (3.48 m ²)	50 ft ² (4.65 m ²)
Rolls per Box	2	1	1
Linear ft (m) per Box	200 (60.96)	50 (15.24)	50 (15.24)
Wt. per Box lb (kg)	63 (28.6)	24 (10.9)	32 (14.5)

Storage

Shelf Life	6 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, keep clean and dry prior to use.
Temperature Range	60°F – 80°F (16°C – 27°C)