

## Features and Components

**Use:** Provides additional reinforcing strength and moisture protection at the lap area of adjoining EPDM sheets, as well as sealing gravel stop flanges to EPDM membrane.

**Materials:** 45 mil (1.14 mm) thick, cured EPDM (ethylene propylene diene monomer) and factory-laminated, self-adhering seam tape.

**Color:** Black



Component

**A**  
Accessory

Single Ply

Type

**MS**  
Membrane Seaming

**FE**  
Flashing Edge

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

## Installation/Application



Self-Adhered

- Prime EPDM membrane and/or metal flange with JM Tape Primer or JM Tape Primer (Low VOC) before applying to JM EPDM Peel & Stick Sealing Strip.
- Do not install in direct contact with asphalt or coal tar pitch.
- Refer to JM EPDM applicator guides or detail drawings for instructions.

## Packaging and Dimensions

Roll Sizes	6" x 100' (15.24 cm x 30.48 m)	9" x 100' (22.86 cm x 30.48 m)	12" x 50' (30.48 cm x 15.24 m)
Thickness: Membrane Tape Total	0.045" (1.14 mm) 0.030" (0.76 mm) 0.075" (1.90 mm)		
Coverage	50 ft <sup>2</sup> (4.65 m <sup>2</sup> )	75 ft <sup>2</sup> (6.97 m <sup>2</sup> )	50 ft <sup>2</sup> (4.65 m <sup>2</sup> )
Rolls per Box	2	1	1
Linear ft (m) per Box	200 (60.96)	100 (30.48)	50 (15.24)
Wt. per Box lb (kg)	51 lb (23.13 kg)	39 lb (17.69 kg)	27 lb (12.25 kg)

## Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, keep clean and dry prior to use.
Temperature Range	60°F – 80°F (16°C – 27°C)

Refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).