

## Features and Components

**Use:** Provides a safe, stable and maintenance-free walkway for quick and easy access to rooftop equipment in high traffic areas.

**Material:** 72 mil (1.83 mm) thick, textured, reinforced, UV-resistant PVC (polyvinyl chloride) with Elvaloy®\* KEE (ketone ethylene ester).

**Color:** Grey

\* Elvaloy is a registered trademark of E. I. du Pont de Nemours and Company or its affiliates.



**Component**

**A**  
Accessory

Single Ply

**Type**

**PT**  
Protection

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<b>Do not use in Multi-Ply systems</b>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<b>Compatible with the selected Single Ply systems above</b>							

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

## Installation/Application



Hot Air Weld

When installing JM PVC Walkpads be sure to:

- Achieve full weld around perimeter of the material
- Install textured side up
- Minimize installing over seams and membrane splices whenever possible
- On mechanically fastened systems, avoid installing over the disc
- Refer to JM PVC applicator guides or detail drawings for instructions

## Packaging and Dimensions

Roll Size ( <i>width x length</i> )	36" x 60' (91.44 cm x 18.29 m)
Nominal Thickness	0.072" (1.83 mm)
Coverage per Roll ( <i>gross</i> )	180 ft <sup>2</sup> (16.72 m <sup>2</sup> )
Weight per Roll	78 lb (35.4 kg)

## Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---