

## Features and Components

**Use:** JM Polyester Mat Protection Slipsheet is intended for use as a separation layer between extruded polystyrene insulation and roofing membrane in protected membrane (inverted) roof assemblies, as well as a separating sheet in some recover systems. It is also used as a protective layer between pavers and JM single ply membrane.

**Material:** 9.0 oz/yd<sup>2</sup> (305.15 g/m<sup>2</sup>) needle-punched, UV-resistant polyester fabric.

**Color:** White



**Component**

**A**  
Accessory

Single Ply

**Type**

**PT**  
Protection

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with all Single Ply systems</i>							

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

## Installation/Application



Loose Laid



Mechanically Fastened

- JM Polyester Mat Protection Slipsheet is typically installed between the overlying extruded polystyrene insulation and JM PVC roofing membrane.
- Refer to JM PVC applicator guides or detail drawings for instructions.

## Packaging and Dimensions

Roll Size	12' wide x 100' long (3.7 m x 30.48 m)
Coverage per Roll	1,200 ft <sup>2</sup> (111.48 m <sup>2</sup> ) (gross)
Weight per Roll	84 lb (38.1 kg)

## Storage

Storage Conditions	Store indoors, out of direct sunlight, in a cool, dry location prior to application.
--------------------	--