


Features and Components

Use: Primarily used as a safety warning line for roof perimeters.

Material: 45 mil thick, reinforced, UV-resistant PVC (polyvinyl chloride) with Elvaloy* KEE (ketone ethylene ester).

Colors: Yellow

* Elvaloy is a registered trademark of E. I. du Pont de Nemours and Company or its affiliates.



Component

A
Accessory

Single Ply

Type

PT
Protection

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
Do not use in Multi-Ply systems									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

- Do not install JM PVC Detail Strip in direct contact with asphalt or coal tar pitch
- Refer to JM PVC applicator guides or detail drawings for instructions

Packaging and Dimensions

Roll Size (<i>width x length</i>)	12' x 150' (30.5 cm x 45.72 m)
Nominal Thickness	0.045" (1.83 mm)
Coverage per Roll (<i>gross</i>)	150 ft ² (13.93 m ²)
Weight per Roll	60 lb (39.0 kg)

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---