

## Features and Components

**Use:** A prefabricated, reinforced 60 mil JM PVC (KEE) square boot in 2" and 4" (5.08 cm and 10.16 cm) sizes for tube-flashing application. Pipe boots minimize the need for field fabrication. Custom sizes and colors are available upon request. Contact your JM representative for minimum order quantity and lead time.

**Material:** JM PVC 60 mil reinforced membrane containing the optimal amount of DuPont™ Elvaloy®\* KEE (Ketone Ethylene Ester) that is factory fabricated into a one-piece square split-pipe boot.

**Color:** White



**Component**

**A**  
Accessory

Single Ply

**Type**

**FP**  
Penetration

**System Compatibility** This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

## Energy and the Environment

Standard		Reflectivity	Emissivity
CRRC®	Initial	0.86	0.86
	3 Yr. Aged	0.70	0.82
CA Title 24	Pass	0.86	0.86
ENERGY STAR®	Initial	0.86	0.82
	3 Yr. Aged	0.70	
LEED® (SRI)	Initial	108	
	3 Yr. Aged	84	
Recycled Content	Post-consumer	0%	
	Post-industrial	0% - 10%	

The LEED® Solar Reflectance Index (SRI) is calculated per ASTM E1980.

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

## Installation/Application



Hot Air Weld

- Do not install JM PVC Split Square Pipe Boots in direct contact with asphalt or coal tar pitch.
- Refer to JM PVC application guides or detail drawings for instructions.

## Packaging and Dimensions

Size/Round Base	2" (5.08 cm) – 16" (40.64 cm) Base 4" (10.16 cm) – 16" (40.64 cm) Base
Height	8" (20.32 cm)
Boots per Box	8
Weight per Box	2" – 7 lb (3.18 kg) 4" – 8.7 lb (3.95 kg)

\* Elvaloy is a registered trademark of E.I. du Pont de Nemours and Company or its affiliates.

Refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the Web at [www.jm.com/roofing](http://www.jm.com/roofing).