

Features and Components

Use: To clean the JM All Season Sprayable Bonding Adhesive accessories including hoses, applicators, extender, and nozzles for temporary or long-term storage. Also to clean and remove over spray of the JM All Season Sprayable Bonding adhesive from membrane seams or necessary areas.

Type: A low-VOC aerosol sprayable cleaner

Color: Clear



Component

CL
Cleaner

Type

AD
Adhesive

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	HW	HA	CA	HW	SA	MF	
Do not use in multi-ply systems									

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
Compatible with the selected Single Ply systems above										

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

Energy and the Environment

Vapor Pressure at 20°C	<1 mmHg
VOC Content*	14 g/l material (calculated)
*Less exempt compounds	

Precautions

Prevention: Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash skin thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves / eye protection / face protection.

Installation/Application



Spray



Natural Fiber Cloth

- Refer to the detailed application instructions and guidelines for proper cleaning and flushing of accessories. Instructions are available online in the JM TPO Application Guide and the JM EPDM Application Guide under the section for JM All Season Sprayable Bonding Adhesive.

Packaging and Coverage

Container Size	13.5 lb canister
Container Weight	13.5 lb/box
Boxes per Pallet	60 boxes/pallet

Storage

Shelf Life	12 months from manufacture date
Storage Conditions	Clean, dry, indoor environment, in a well-ventilated area, and in an unopened container, tightly sealed.
Temperature Range	60°F - 80°F (16°C - 27°C). Do not let freeze.