

Features and Components

- Use:** Provides a visual and physical safety warning on roof top areas of caution and potential hazards including designation of the roof perimeter.
- Material:** 55 mil (1.40 mm) total thickness, comprised of 30 mil (0.76 mm) yellow non-reinforced TPO membrane laminated to 25 mil (0.64 mm) white cured seaming tape.
- Colors:** Yellow



Component

A
Accessory

Single Ply

Type

PT
Protection

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
<i>Do not use in Multi-Ply systems</i>									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
<i>Compatible with the selected Single Ply systems above</i>							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Energy and Environment

LEED®	Recycled Content: Post-consumer: 0% Post-industrial: 0%
-------	---

Physical Properties

Property	JM TPO Safety Strip
Weight per Unit	0.52 lb/ft ² (2.54 kg/m ²)

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

When installing JM TPO Safety Strip be sure to:

- Prime with JM TPO Membrane Primer or JM Single Ply Membrane Primer (Low VOC) according to their application instructions to prepare the membrane for the safety strip.
- Minimize installing over seams and membrane splices whenever possible.
- Refer to JM TPO applicator guide or detail drawings for instructions.

Packaging and Dimensions

Roll Size	5.5" x 100' (14 cm x 30.48 m)
Thickness	55 mil (1.40 mm)
Rolls per Box	1
Weight per Roll	19 lb (8.6 kg)

Storage

Shelf Life	18 months when stored under appropriate conditions. If stored in non-optimal conditions shelf life may be reduced.
Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
Temperature Range	Store between 60 – 80 °F (15.6 – 26.7 °C)