

## Features and Components

**Use:** Provides a safe, stable and maintenance-free walkway for quick and easy access to rooftop equipment in high traffic areas. The safety yellow color serves to provide a highly visible warning to areas of caution or hazards on the rooftop.

**Material:** 150 mil (3.81 mm) thick, textured non-reinforced TPO (thermoplastic polyolefin).

**Color:** Yellow



Component

<b>A</b>
Accessory
Single Ply
Type
<b>PT</b>
Protection

## System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	HW	HA	CA	HW	SA	MF
<b>Do not use in multi-ply systems</b>								

Single Ply	TPO				PVC			EPDM		
	MF	AD	SA	IW	MF	AD	IW	MF	AD	BA
<b>Compatible with the selected single ply systems above</b>										

**Key:** HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened IW = Induction Weld BA = Ballasted AD = Adhered

## Energy and Environment

LEED®	Recycled Content: Post-consumer: 0% Post-industrial: 50%
-------	--

## Physical Properties

Property	JM TPO Walkpads
Weight per Unit	0.46 lb/ft <sup>2</sup> (2.27 kg/m <sup>2</sup> )

## Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Technical specifications as shown in this literature are intended to be used as general guidelines only. Please refer to the Safety Data Sheet and product label prior to using this product. The Safety Data Sheet is available by calling (800) 922-5922 or on the web at [www.jm.com/roofing](http://www.jm.com/roofing). The physical and chemical properties of the product listed herein represent typical, average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Check with the regional sales representative nearest you for current information.

All Johns Manville products are sold subject to Johns Manville's standard Terms and Conditions, which includes a Limited Warranty and Limitation of Remedy. For a copy of the Johns Manville standard Terms and Conditions or for information on other Johns Manville roofing products and systems, visit [www.jm.com/terms-conditions](http://www.jm.com/terms-conditions).

## Installation/Application



When installing JM TPO Safety Walkpads be sure to:

- Achieve full weld around perimeter of the material.
- Install textured side up.
- Minimize installing over seams and membrane splices whenever possible.
- On mechanically fastened systems, avoid installing over the disc.
- Refer to JM TPO applicator guides or detail drawings for instructions.

## Packaging and Dimensions

Roll Size	30' x 50' (76.2 cm x 15.24 m)
Thickness	0.150" (3.81 mm)
Rolls per Container	1
Coverage/Container	125 ft <sup>2</sup> (11.61 m <sup>2</sup> ) (gross)
Weight per Roll	58 lb (26.3 kg)
Rolls per Pallet	16

## Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---