

Features and Components

- Use:** A smooth, cone-shaped boot, for traditional or split-pipe flashing applications to securely seal the penetration. Pipe boots eliminate the need for field fabrication.
- Material:** Flexible, smooth, non-reinforced TPO (thermoplastic polyolefin) cone-shaped boot with preformed flange.
- Colors:** White; Grey; and Tan



Component
A Accessory
Single Ply
Type
FP Penetration

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
Do not use with Multi-Ply systems								

Single Ply	TPO		PVC		EPDM		
	MF	AD	MF	AD	MF	AD	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened AD = Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Hot Air Weld

- Each boot has a cutting guide for easy reference and diameter measurements.
- Do not install JM TPO Pipe Boots in direct contact with asphalt.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Sizes*	1" to 6" (2.5 cm to 15.2 cm)
Boots per Box	10
Weight per Boot	0.85 lb (0.38 kg)
Weight per Box	9 lb (4.1 kg)
Thickness	0.060" (1.52 mm)

* Standard size pipe clamps covering the largest possible range (6" diameter) are included for each pipe boot. Dimensions less than 1.5" (3.8 cm) diameter may require alternative clamps.

Storage

Storage Conditions	Store indoors, out of direct sunlight, and keep clean and dry prior to application.
--------------------	---