

Features and Components

Use: To strip in metal flanges on JM TPO Membrane systems or as directed by JM technical services.

Materials: 30 mil (0.76 mm) thick, non-reinforced TPO (thermoplastic polyolefin membrane with a 30 mil (0.76 mm) thick, factory-applied peel and stick adhesive tape.

Colors: White; Grey; and Tan



Component

A
Accessory

Single Ply

Type

FW
Flashing Wall

FE
Flashing Edge

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS				
	HA	CA	CA	HW	HA	CA	HW	SA	MF
Do not use in Multi-Ply systems									

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Self-Adhered

- Prime TPO Membrane with JM TPO Membrane Primer or JM Single Ply Membrane Primer (Low VOC) before applying JM TPO Cover Tape.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Sizes		Coverage
6" x 100' (15.24 cm x 30.48 m)		50 ft ² (4.65 m ²)
10" x 100' (25.4 cm x 30.48 m)		83.3 ft ² (7.74 m ²)
Thickness:		
Membrane	0.030" (0.76 mm)	
Tape	0.030" (0.76 mm)	
Total	0.060" (1.52 mm)	
Roll Widths	6"	10"
Rolls per Box	2	1
Linear ft (m) per Box	200 (60.96)	100 (30.48)

Storage

Shelf Life	18 months from manufacture date
Storage Conditions	Store indoors, out of direct sunlight, in original unopened containers
Temperature Range	60°F – 80°F (16°C – 27°C)