

Features and Components

Use: To easily form flashings around corners and penetrations. Specifically designed for use in areas that cannot be properly detailed with TPO field membrane.

Material: Flexible, non-reinforced TPO (thermoplastic polyolefin).

Colors: White; Grey; and Tan



Component
A
Accessory
Single Ply

System Compatibility This product may be used as a component in the following systems. Please reference product application for specific installation methods and information.

Multi-Ply	BUR		APP		SBS			
	HA	CA	CA	HW	HA	CA	HW	SA
Do not use with Multi-Ply systems								

Single Ply	TPO		PVC		EPDM		
	MF	FA	MF	FA	MF	FA	BA
Compatible with the selected Single Ply systems above							

Key: HA = Hot Applied CA = Cold Applied HW = Heat Weldable SA = Self Adhered MF = Mechanically Fastened FA = Fully Adhered BA = Ballasted

Physical Properties

Property	JM TPO Detail Membrane
Tear Resistance (<i>min</i>)	300 lb/in (52.5 kN/m)
Weight per Unit	0.36 lb/ft ² (1.25 kg/m ²)

Peak Advantage® Guarantee Information

Systems
Approved for use in any JM Peak Advantage Guarantee System

Installation/Application



Fully Adhered

Hot Air Weld

- Do not install JM TPO Detail Membrane in direct contact with asphalt.
- Refer to JM TPO applicator guides or detail drawings for instructions.

Packaging and Dimensions

Roll Sizes*	24" x 50' (61 cm x 15.24 m)	48" x 50' (122 cm x 15.24 m)
Nominal Thickness	0.060" (1.5 mm) ±10%	
Coverage per Roll	100 ft ² (9.29 m ²) (<i>gross</i>)	200 ft ² (18.58 m ²) (<i>gross</i>)
Weight per Roll (<i>approx</i>)	36 lb (16.3 kg)	72 lb (32.7 kg)

* 48" width is available in white only.

Storage

Storage Conditions	Store indoors, out of direct sunlight, in a cool, dry location
--------------------	--